

JZ-500 flexible, number coded, meter marking



Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
10047	18 G 0,75	12,2	130,0	257,0	18
10533	19 G 0,75	12,7	137,0	264,0	18
10048	20 G 0,75	12,7	144,0	286,0	18
10049	21 G 0,75	13,5	151,0	320,0	18
10050	25 G 0,75	14,5	180,0	365,0	18
10534	27 G 0,75	15,2	195,0	382,0	18
10051	32 G 0,75	16,1	230,0	455,0	18
10052	34 G 0,75	16,7	245,0	510,0	18
10182	37 G 0,75	17,2	266,0	537,0	18
10053	40 G 0,75	18,0	288,0	595,0	18
10054	41 G 0,75	18,0	296,0	607,0	18
10055	42 G 0,75	18,0	302,0	612,0	18
10056	50 G 0,75	19,8	360,0	735,0	18
10057	61 G 0,75	21,2	439,0	845,0	18
10178	65 G 0,75	22,5	468,0	895,0	18
10058	80 G 0,75	24,3	576,0	1070,0	18
10059	100 G 0,75	27,0	720,0	1322,0	18
10060	2 x 1	5,6	19,2	60,0	17
10061	3 G 1	6,1	29,0	72,0	17
10062	3 x 1	6,1	29,0	72,0	17
10063	4 G 1	6,6	38,4	86,0	17
10064	4 x 1	6,6	38,4	86,0	17
10065	5 G 1	7,5	48,0	104,0	17
10066	5 x 1	7,5	48,0	104,0	17
10067	6 G 1	8,1	58,0	125,0	17
10068	7 G 1	8,1	67,0	141,0	17
10069	7 x 1	8,1	67,0	141,0	17
10070	8 G 1	9,6	77,0	175,0	17
10071	9 G 1	10,6	86,0	200,0	17
10180	10 G 1	10,6	96,0	217,0	17
10170	10 x 1	10,6	96,0	217,0	17
10072	12 G 1	10,8	115,0	230,0	17
10073	12 x 1	10,8	115,0	230,0	17
10074	14 G 1	11,4	134,0	271,0	17
10075	16 G 1	12,3	154,0	300,0	17
10076	18 G 1	12,9	173,0	343,0	17
10174	18 x 1	12,9	173,0	343,0	17
10197	19 G 1	13,0	182,0	355,0	17
10077	20 G 1	13,7	192,0	375,0	17
10184	20 x 1	13,7	192,0	375,0	17
10179	21 G 1	14,4	205,0	420,0	17
10175	24 G 1	14,7	230,0	440,0	17
10078	25 G 1	15,6	240,0	485,0	17
10176	25 x 1	15,6	240,0	485,0	17
10196	26 G 1	15,6	252,0	500,0	17
10198	27 G 1	15,8	259,0	534,0	17
10168	30 x 1	16,4	308,0	550,0	17
10079	34 G 1	17,9	326,0	650,0	17
10080	36 G 1	17,9	346,0	668,0	17
10199	37 G 1	18,4	355,0	701,0	17
10081	40 G 1	19,4	384,0	755,0	17
10167	40 x 1	19,4	384,0	755,0	17
10082	41 G 1	19,4	394,0	770,0	17
10083	42 G 1	19,4	403,0	810,0	17
10084	50 G 1	21,2	480,0	936,0	17
10085	56 G 1	22,1	538,0	920,0	17
10086	61 G 1	22,7	586,0	1100,0	17
10087	65 G 1	24,2	628,0	1180,0	17
10088	80 G 1	26,2	768,0	1294,0	17
10089	100 G 1	29,2	960,0	1644,0	17
10090	2 x 1,5	6,4	29,0	70,0	16
10091	3 G 1,5	6,8	43,0	90,0	16
10092	3 x 1,5	6,8	43,0	90,0	16
10093	4 G 1,5	7,6	58,0	109,0	16
10094	4 x 1,5	7,6	58,0	109,0	16
10095	5 G 1,5	8,3	72,0	131,0	16
10096	5 x 1,5	8,3	72,0	131,0	16
10097	6 G 1,5	9,2	86,0	157,0	16
10098	7 G 1,5	9,2	101,0	184,0	16
10099	7 x 1,5	9,2	101,0	184,0	16
10100	8 G 1,5	10,6	115,0	216,0	16
10101	9 G 1,5	12,0	129,0	259,0	16
10181	10 G 1,5	12,0	144,0	275,0	16
10102	11 G 1,5	12,2	158,0	300,0	16
10103	12 G 1,5	12,2	173,0	309,0	16
10104	12 x 1,5	12,2	173,0	309,0	16
10105	14 G 1,5	13,0	202,0	345,0	16
10106	16 G 1,5	13,9	230,0	386,0	16
10107	18 G 1,5	14,8	259,0	440,0	16
10185	19 G 1,5	15,2	279,0	445,0	16
10108	20 G 1,5	15,5	288,0	490,0	16
10109	21 G 1,5	16,4	302,0	555,0	16

Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
10110	25 G 1,5	17,8	360,0	620,0	16
10535	27 G 1,5	19,0	389,0	670,0	16
10111	32 G 1,5	19,5	461,0	790,0	16
10112	34 G 1,5	20,2	490,0	830,0	16
10536	37 G 1,5	20,2	533,0	892,0	16
10113	41 G 1,5	22,0	576,0	996,0	16
10114	42 G 1,5	22,0	605,0	1007,0	16
10115	50 G 1,5	24,2	720,0	1250,0	16
10116	56 G 1,5	25,1	806,0	1332,0	16
10117	61 G 1,5	25,8	878,0	1440,0	16
10187	65 G 1,5	27,4	936,0	1602,0	16
10118	80 G 1,5	29,8	1152,0	1871,0	16
10119	100 G 1,5	33,0	1440,0	2353,0	16
10120	2 x 2,5	7,8	48,0	112,0	14
10121	3 G 2,5	8,3	72,0	148,0	14
10122	3 x 2,5	8,3	72,0	148,0	14
10123	4 G 2,5	9,2	96,0	178,0	14
10124	4 x 2,5	9,2	96,0	178,0	14
10125	5 G 2,5	10,1	120,0	221,0	14
10126	5 x 2,5	10,1	120,0	221,0	14
10127	7 G 2,5	11,2	168,0	306,0	14
10128	7 x 2,5	11,2	168,0	306,0	14
10129	8 G 2,5	13,4	192,0	363,0	14
10130	12 G 2,5	15,1	288,0	498,0	14
10131	14 G 2,5	16,2	336,0	569,0	14
10132	18 G 2,5	18,2	432,0	764,0	14
10133	21 G 2,5	20,2	504,0	914,0	14
10134	25 G 2,5	22,1	600,0	1044,0	14
10135	34 G 2,5	25,2	816,0	1470,0	14
10136	42 G 2,5	27,2	1008,0	1790,0	14
10137	50 G 2,5	30,0	1200,0	2095,0	14
10138	61 G 2,5	32,2	1464,0	2750,0	14
10139	100 G 2,5	41,2	2400,0	4450,0	14
10140	2 x 4	9,2	77,0	195,0	12
10141	3 G 4	9,7	115,0	230,0	12
10142	4 G 4	10,8	154,0	295,0	12
10143	5 G 4	12,1	192,0	361,0	12
10144	7 G 4	13,4	269,0	458,0	12
10145	8 G 4	13,4	307,0	590,0	12
10146	12 G 4	18,3	461,0	790,0	12
10147	3 G 6	11,9	173,0	355,0	10
10148	4 G 6	13,0	230,0	424,0	10
10149	5 G 6	14,7	288,0	525,0	10
10150	7 G 6	16,2	403,0	625,0	10
10151	3 G 10	15,1	288,0	540,0	8
10152	4 G 10	16,7	384,0	701,0	8
10153	5 G 10	18,6	480,0	858,0	8
10154	7 G 10	20,7	672,0	1106,0	8
10190	3 G 16	18,0	461,0	827,0	6
10155	4 G 16	20,0	614,0	1035,0	6
10156	5 G 16	22,4	768,0	1259,0	6
10157	7 G 16	24,8	1075,0	1780,0	6
10191	3 G 25	22,2	720,0	1186,0	4
10158	4 G 25	24,7	960,0	1582,0	4
10159	5 G 25	27,6	1200,0	1999,0	4
10160	7 G 25	30,5	1680,0	2825,0	4
10192	3 x 35	25,4	1008,0	1585,0	2
10161	4 G 35	28,0	1344,0	2105,0	2
10162	5 G 35	31,3	1680,0	2633,0	2
10193	3 G 50	31,4	1440,0	2550,0	1
10163	4 G 50	34,7	1920,0	2940,0	1
10188	5 G 50	38,7	2400,0	2936,0	1
10194	3 G 70	38,5	2016,0	3180,0	2/0
10164	4 G 70	42,7	2688,0	4090,0	2/0
10189	5 G 70	47,6	3360,0	5443,0	2/0
10195	3 G 95	43,2	2736,0	4680,0	3/0
10165	4 G 95	47,9	3648,0	5540,0	3/0
10333	5 G 95	52,7	4560,0	6931,0	3/0
10166	4 G 120	52,6	4608,0	7000,0	4/0
13139	4 G 150	62,3	5760,0	8340,0	300 kcmil
13140	4 G 185	67,0	7104,0	9904,0	350 kcmil

Dimensions and specifications may be changed without prior notice. (RA01)