

H05VV5-F (NYSLYÖ-JZ) flexible, number coded,

oil resistant, meter marking



Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
13119	2 x 1	6,6	19,0	66,0	17
13025	3 G 1	7,0	29,0	78,0	17
13026	4 G 1	7,6	38,0	104,0	17
13027	5 G 1	8,7	48,0	123,0	17
13028	6 G 1	9,5	58,0	152,0	17
13029	7 G 1	10,2	67,0	183,0	17
13931	8 G 1	11,0	77,0	220,0	17
13030	9 G 1	12,1	86,0	230,0	17
13031	12 G 1	12,7	115,0	269,0	17
13932	14 G 1	13,3	134,0	361,0	17
13032	18 G 1	15,0	173,0	400,0	17
13933	19 G 1	15,0	183,0	413,0	17
13033	25 G 1	18,0	240,0	546,0	17
13934	27 G 1	18,0	259,0	582,0	17
13034	34 G 1	20,6	326,0	724,0	17
13124	36 G 1	21,0	348,0	775,0	17
13935	37 G 1	21,0	355,0	785,0	17
13127	41 G 1	22,5	392,0	822,0	17
13035	50 G 1	24,5	480,0	1052,0	17
13036	61 G 1	26,0	586,0	1265,0	17
13936	65 G 1	28,1	624,0	1315,0	17
13120	2 x 1,5	7,3	29,0	77,0	16
13037	3 G 1,5	7,9	43,0	97,0	16
13038	4 G 1,5	8,7	58,0	128,0	16
13039	5 G 1,5	9,6	72,0	149,0	16
13040	6 G 1,5	10,7	86,0	196,0	16
13041	7 G 1,5	11,8	101,0	216,0	16
13937	8 G 1,5	13,2	115,0	271,0	16
13042	9 G 1,5	13,5	130,0	282,0	16
13043	12 G 1,5	14,4	173,0	324,0	16
13121	14 G 1,5	15,3	202,0	372,0	16
13044	18 G 1,5	17,2	259,0	485,0	16
13938	19 G 1,5	17,2	274,0	495,0	16
13045	25 G 1,5	21,7	360,0	671,0	16
13939	27 G 1,5	21,7	389,0	695,0	16
13046	32 G 1,5	22,4	461,0	820,0	16
13047	34 G 1,5	24,1	490,0	881,0	16
13940	36 G 1,5	24,4	518,0	905,0	16
13941	37 G 1,5	24,4	532,0	920,0	16
13128	41 G 1,5	26,3	590,0	1085,0	16
13048	50 G 1,5	28,9	720,0	1381,0	16
13049	61 G 1,5	30,8	878,0	1640,0	16
13942	65 G 1,5	32,2	963,0	1730,0	16

Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
13943	2 x 2,5	9,1	48,0	110,0	14
13050	3 G 2,5	9,6	72,0	154,0	14
13051	4 G 2,5	10,8	96,0	212,0	14
13052	5 G 2,5	11,6	120,0	242,0	14
13053	7 G 2,5	14,2	168,0	350,0	14
13945	8 G 2,5	16,1	192,0	379,0	14
13054	12 G 2,5	17,7	288,0	543,0	14
13946	14 G 2,5	19,0	336,0	611,0	14
13055	18 G 2,5	21,4	432,0	787,0	14
13056	25 G 2,5	26,1	600,0	1175,0	14
13947	27 G 2,5	26,2	648,0	1280,0	14
13057	34 G 2,5	29,5	816,0	1529,0	14
13948	36 G 2,5	29,6	864,0	1791,0	14
13949	41 G 2,5	32,0	984,0	1905,0	14
13058	50 G 2,5	35,0	1200,0	2290,0	14
13059	61 G 2,5	37,1	1464,0	2724,0	14

Dimensions and specifications may be changed without prior notice. (RA01)

Our Service on the Internet

The screenshot shows the HELUKABEL website interface. At the top, there is a navigation menu with links for Download centre, Logistic centre, Company, Products, Quality, News, Contact, Service, Opinion, and Imprint. Below the menu, there is a search bar and a 'You are here' breadcrumb trail. The main content area features a 'News' section with links to Fairs, Job posting, Special offer's, and Press Contact. A 'Fairs' section is also visible, containing several images of trade fair booths. On the right side, there is a 'HELUKABEL world-wide' section with a world map and a dropdown menu labeled 'please select...'. The HELUKABEL logo is prominently displayed at the top right of the page.

Trade fair appointments

In the Internet, you will find the trade fairs we are participating in, both in Germany and abroad. Please visit our Website and arrange an appointment with us. We are looking forward to your visit.

www.helukabel.de