

UNIPUR® flexible at low temperature, with customer markings, halogen-free, wear resistant, robust, meter marking



A

| Part No. | No. cores x cross-sec. mm ² | Outer ø app. mm | Cop. weight kg / km | Weight app. kg / km | AWG-No. | Part No. | No. cores x cross-sec. mm ² | Outer ø app. mm | Cop. weight kg / km | Weight app. kg / km | AWG-No. |
|----------|--|-----------------|---------------------|---------------------|---------|----------|--|-----------------|---------------------|---------------------|---------|
| 1833_ | 2 x 1 | 6,8 | 19,2 | 59,0 | 17 | 1855_ | 2 x 2,5 | 10,0 | 48,0 | 120,0 | 14 |
| 1834_ | 3 G 1 | 7,2 | 29,0 | 70,0 | 17 | 1856_ | 3 G 2,5 | 10,5 | 72,0 | 148,0 | 14 |
| 1835_ | 4 G 1 | 7,8 | 38,0 | 87,0 | 17 | 1857_ | 4 G 2,5 | 11,8 | 96,0 | 184,0 | 14 |
| 1836_ | 5 G 1 | 8,8 | 48,0 | 100,0 | 17 | 1858_ | 5 G 2,5 | 13,0 | 120,0 | 224,0 | 14 |
| 1837_ | 6 G 1 | 9,6 | 58,0 | 131,0 | 17 | 1859_ | 7 G 2,5 | 14,7 | 168,0 | 301,0 | 14 |
| 1838_ | 7 G 1 | 10,5 | 67,0 | 182,0 | 17 | 1860_ | 12 G 2,5 | 18,0 | 288,0 | 489,0 | 14 |
| 1839_ | 12 G 1 | 13,0 | 115,0 | 230,0 | 17 | | | | | | |
| 1840_ | 18 G 1 | 15,1 | 173,0 | 325,0 | 17 | 1861_ | 2 x 4 | 11,6 | 77,0 | 149,0 | 12 |
| 1841_ | 25 G 1 | 18,7 | 240,0 | 476,0 | 17 | 1862_ | 3 G 4 | 12,3 | 115,0 | 240,0 | 12 |
| 1842_ | 34 G 1 | 21,6 | 326,0 | 616,0 | 17 | 1865_ | 4 G 4 | 13,7 | 154,0 | 297,0 | 12 |
| 1843_ | 41 G 1 | 23,2 | 394,0 | 724,0 | 17 | 1864_ | 5 G 4 | 15,2 | 192,0 | 360,0 | 12 |
| | | | | | | 1865_ | 7 G 4 | 20,8 | 268,0 | 540,0 | 12 |
| 1844_ | 2 x 1,5 | 8,3 | 29,0 | 92,0 | 16 | 1866_ | 2 x 6 | 13,2 | 115,0 | 240,0 | 10 |
| 1845_ | 3 G 1,5 | 8,8 | 43,0 | 108,0 | 16 | 1867_ | 3 G 6 | 14,2 | 173,0 | 370,0 | 10 |
| 1846_ | 4 G 1,5 | 9,9 | 58,0 | 144,0 | 16 | 1868_ | 4 G 6 | 15,8 | 230,0 | 472,0 | 10 |
| 1847_ | 5 G 1,5 | 10,8 | 72,0 | 168,0 | 16 | 1869_ | 5 G 6 | 17,5 | 288,0 | 581,0 | 10 |
| 1848_ | 6 G 1,5 | 11,9 | 86,0 | 201,0 | 16 | 1870_ | 7 G 6 | 22,0 | 403,0 | 698,0 | 10 |
| 1849_ | 7 G 1,5 | 12,9 | 101,0 | 230,0 | 16 | | | | | | |
| 1850_ | 12 G 1,5 | 14,7 | 173,0 | 306,0 | 16 | 1871_ | 3 G 10 | 18,6 | 288,0 | 560,0 | 8 |
| 1851_ | 18 G 1,5 | 17,9 | 259,0 | 464,0 | 16 | 1872_ | 4 G 10 | 20,5 | 384,0 | 718,0 | 8 |
| 1852_ | 25 G 1,5 | 20,8 | 360,0 | 641,0 | 16 | 1873_ | 5 G 10 | 22,7 | 480,0 | 896,0 | 8 |
| 1853_ | 34 G 1,5 | 24,9 | 490,0 | 857,0 | 16 | | | | | | |
| 1854_ | 41 G 1,5 | 26,7 | 590,0 | 1010,0 | 16 | 1874_ | 3 G 16 | 23,5 | 461,0 | 940,0 | 6 |
| | | | | | | 1875_ | 4 G 16 | 25,7 | 614,0 | 1068,0 | 6 |
| | | | | | | 1876_ | 5 G 16 | 28,5 | 768,0 | 1810,0 | 6 |

Dimensions and specifications may be changed without prior notice. (RA02)

Our Service on the Internet

The screenshot shows the HELUKABEL website navigation menu. The 'Service' dropdown is open, listing various options. The 'HELU-Newsletter' option is highlighted. Below the menu, there is a search bar and a 'HELUKABEL world-wide' section with a world map and a dropdown menu.

HELU Newsletter

Take advantage of our HELU Newsletter service: It's free and without obligation. We report on HELUKABEL's® broad product spectrum, such as new products, trade fairs, industry news and much more.

www.helukabel.de