

# Yö-C-PURÖ-JZ tear and coolant resistant, Cu-screened, with inner sheath, increased oil resistant, EMC-preferred type, meter marking



Part No.	No. cores x cross-sec. mm <sup>2</sup>	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
21451	2 x 1	7,7	54,0	98,0	17
21452	3 G 1	8,0	64,0	102,0	17
21453	4 G 1	8,6	76,0	145,0	17
21454	5 G 1	9,1	89,0	170,0	17
21456	7 G 1	11,0	114,0	220,0	17
21457	8 G 1	12,6	130,0	270,0	17
21458	10 G 1	12,6	156,0	330,0	17
21459	12 G 1	13,1	186,0	350,0	17
21460	14 G 1	13,8	198,0	402,0	17
21461	16 G 1	14,6	214,0	420,0	17
21462	18 G 1	15,6	284,0	515,0	17
21463	20 G 1	16,4	325,0	545,0	17
21465	25 G 1	18,9	387,0	690,0	17
21468	34 G 1	20,9	500,0	912,0	17
21469	41 G 1	22,3	578,0	1070,0	17
21470	50 G 1	24,6	681,0	1318,0	17
21474	2 x 1,5	8,2	64,0	130,0	16
21475	3 G 1,5	8,6	82,0	152,0	16
21476	4 G 1,5	9,3	99,0	167,0	16
21477	5 G 1,5	10,4	123,0	203,0	16
21479	7 G 1,5	12,0	148,0	305,0	16
21480	8 G 1,5	12,9	172,0	335,0	16
21481	10 G 1,5	14,2	198,0	422,0	16
21482	12 G 1,5	14,6	274,0	435,0	16
21483	14 G 1,5	15,4	294,0	480,0	16
21484	16 G 1,5	16,1	318,0	525,0	16
21485	18 G 1,5	17,2	386,0	642,0	16
21487	21 G 1,5	19,0	447,0	722,0	16
21489	25 G 1,5	20,8	531,0	803,0	16
21492	34 G 1,5	23,2	671,0	1068,0	16
21494	42 G 1,5	26,1	890,0	1370,0	16
21495	50 G 1,5	27,4	997,0	1677,0	16
21499	2 x 2,5	9,8	110,0	180,0	14
21500	3 G 2,5	10,7	148,0	215,0	14
21501	4 G 2,5	11,4	169,0	268,0	14
21502	5 G 2,5	12,5	220,0	349,0	14
21503	7 G 2,5	14,9	284,0	406,0	14
21504	12 G 2,5	18,4	470,0	720,0	14

Part No.	No. cores x cross-sec. mm <sup>2</sup>	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
21507	2 x 4	12,0	124,0	300,0	12
21508	3 G 4	12,6	178,0	340,0	12
21509	4 G 4	14,2	234,0	408,0	12
21510	5 G 4	15,6	284,0	504,0	12
21511	7 G 4	17,1	321,0	640,0	12
21512	3 G 6	14,8	245,0	453,0	10
21513	4 G 6	16,1	316,0	560,0	10
21514	5 G 6	18,0	442,0	700,0	10
21515	7 G 6	19,6	530,0	905,0	10
21516	3 G 10	18,2	367,0	750,0	8
21517	4 G 10	20,3	549,0	1023,0	8
21518	5 G 10	22,4	604,0	1114,0	8
21519	7 G 10	24,7	820,0	1505,0	8
21521	4 G 16	23,4	807,0	1385,0	6
21522	5 G 16	26,0	940,0	1550,0	6
21524	4 G 25	29,7	1169,0	1894,0	4
21525	5 G 25	33,0	1420,0	2272,0	4
21526	4 G 35	33,9	1680,0	2395,0	2
21527	5 G 35	37,5	2020,0	2890,0	2
21528	4 G 50	39,0	2370,0	3312,0	1
21529	5 G 50	43,4	2880,0	4100,0	1
21530	4 G 70	46,6	3257,0	4605,0	2/0
21531	5 G 70	51,1	4032,0	5710,0	2/0
21532	4 G 95	50,9	4060,0	6055,0	3/0
21533	5 G 95	55,9	5244,0	7520,0	3/0
21534	4 G 120	55,5	5231,0	7318,0	4/0

Dimensions and specifications may be changed without prior notice. (RA02)

## Our Service on the Internet

### Metal quotes

On our Internet site, you will find the current metal prices for copper, brass, lead and aluminium as well as DEL prices developments and the dollar prices over the last few months.

[www.helukabel.de](http://www.helukabel.de)