

# JZ-500 HMH flexible control cable, halogen-free, extremely fire resistant, oil resistant<sup>1)</sup>, meter marking



Part No.	No. cores x cross-sec. mm <sup>2</sup>	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
11221	2 x 0,75	5,2	14,4	47,0	18
11222	3 G 0,75	5,5	21,6	56,0	18
11335	3 x 0,75	5,5	21,6	56,0	18
11223	4 G 0,75	6,2	29,0	69,0	18
11336	4 x 0,75	6,2	29,0	69,0	18
11224	5 G 0,75	6,8	36,0	83,0	18
11337	5 x 0,75	6,8	36,0	83,0	18
11225	7 G 0,75	8,1	50,0	114,0	18
11338	7 x 0,75	8,1	50,0	114,0	18
11226	8 G 0,75	8,9	58,0	136,0	18
11227	10 G 0,75	9,6	72,0	172,0	18
11228	12 G 0,75	9,9	86,0	183,0	18
11229	16 G 0,75	11,5	115,0	241,0	18
11230	18 G 0,75	11,9	130,0	266,0	18
11231	20 G 0,75	12,6	144,0	291,0	18
11232	25 G 0,75	14,1	180,0	374,0	18
11233	30 G 0,75	15,4	216,0	450,0	18
11234	34 G 0,75	16,4	245,0	517,0	18
11235	37 G 0,75	17,2	260,0	541,0	18
11236	41 G 0,75	17,6	296,0	611,0	18
11237	42 G 0,75	17,6	302,0	621,0	18
11238	50 G 0,75	19,8	360,0	742,0	18
11239	61 G 0,75	20,9	439,0	853,0	18
11240	65 G 0,75	21,5	468,0	909,0	18

Part No.	No. cores x cross-sec. mm <sup>2</sup>	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
11277	2 x 2,5	7,6	48,0	118,0	14
11278	3 G 2,5	8,3	72,0	151,0	14
11279	4 G 2,5	9,1	96,0	181,0	14
11280	5 G 2,5	10,2	120,0	224,0	14
11281	7 G 2,5	12,1	168,0	316,0	14
11282	8 G 2,5	13,2	192,0	370,0	14
11283	10 G 2,5	14,7	240,0	451,0	14
11284	12 G 2,5	15,2	288,0	499,0	14
11285	16 G 2,5	17,5	384,0	720,0	14
11286	18 G 2,5	18,1	432,0	769,0	14
11287	20 G 2,5	18,7	480,0	911,0	14
11288	25 G 2,5	22,2	600,0	1047,0	14
11289	30 G 2,5	23,7	720,0	1280,0	14
11290	2 x 4	9,2	77,0	199,0	12
11291	3 G 4	9,9	115,0	247,0	12
11292	4 G 4	11,0	154,0	299,0	12
11293	5 G 4	12,1	192,0	369,0	12
11294	7 G 4	13,3	269,0	463,0	12
11295	8 G 4	15,9	307,0	601,0	12
11296	10 G 4	17,3	384,0	698,0	12
11297	12 G 4	18,3	461,0	790,0	12
11298	16 G 4	20,2	614,0	1130,0	12
11299	18 G 4	21,8	691,0	1280,0	12

11241	2 x 1	5,5	19,2	63,0	17
11242	3 G 1	6,0	29,0	74,0	17
11339	3 x 1	6,0	29,0	74,0	17
11243	4 G 1	6,6	38,4	90,0	17
11244	4 x 1	6,6	38,4	90,0	17
11245	7 G 1	8,6	67,0	151,0	17
11246	8 G 1	9,4	77,0	184,0	17
11247	10 G 1	10,4	96,0	224,0	17
11248	12 G 1	10,7	115,0	243,0	17
11249	16 G 1	12,0	154,0	314,0	17
11250	18 G 1	12,7	173,0	361,0	17
11251	20 G 1	13,5	192,0	387,0	17
11252	25 G 1	15,2	240,0	496,0	17
11253	34 G 1	17,4	326,0	670,0	17
11254	37 G 1	18,4	355,0	713,0	17
11255	41 G 1	18,9	394,0	784,0	17
11256	42 G 1	18,9	403,0	824,0	17
11257	50 G 1	21,0	480,0	952,0	17
11258	61 G 1	22,2	586,0	1140,0	17
11259	65 G 1	22,8	628,0	1201,0	17

11300	2 x 6	10,8	115,0	266,0	10
11301	3 G 6	11,7	173,0	360,0	10
11302	4 G 6	13,0	230,0	429,0	10
11303	5 G 6	14,5	288,0	529,0	10
11304	7 G 6	16,0	403,0	631,0	10
11305	2 x 10	14,0	192,0	440,0	8
11306	3 G 10	15,0	288,0	550,0	8
11307	4 G 10	16,8	384,0	708,0	8
11308	5 G 10	18,7	480,0	860,0	8
11309	7 G 10	20,6	672,0	1124,0	8
11310	2 x 16	16,5	307,0	642,0	6
11311	3 G 16	17,6	461,0	830,0	6
11312	4 G 16	19,7	614,0	1060,0	6
11313	5 G 16	21,9	768,0	1270,0	6
11314	7 G 16	24,4	1075,0	1794,0	6
11315	3 G 25	22,5	720,0	1190,0	4
11316	4 G 25	25,2	960,0	1594,0	4
11317	5 G 25	27,9	1200,0	2014,0	4

11260	2 x 1,5	6,3	29,0	70,0	16
11261	3 G 1,5	6,7	43,0	94,0	16
11341	3 x 1,5	6,7	43,0	94,0	16
11262	4 G 1,5	7,3	58,0	112,0	16
11263	5 G 1,5	8,2	72,0	141,0	16
11264	7 G 1,5	9,8	101,0	191,0	16
11265	8 G 1,5	10,6	115,0	224,0	16
11266	10 G 1,5	11,7	144,0	282,0	16
11267	12 G 1,5	12,1	173,0	311,0	16
11268	16 G 1,5	13,6	230,0	392,0	16
11269	18 G 1,5	14,5	259,0	450,0	16
11270	20 G 1,5	15,2	288,0	497,0	16
11271	25 G 1,5	17,8	360,0	630,0	16
11272	34 G 1,5	19,8	490,0	842,0	16
11273	37 G 1,5	20,2	533,0	897,0	16
11274	50 G 1,5	23,7	720,0	1277,0	16
11275	61 G 1,5	25,3	878,0	1460,0	16
11276	65 G 1,5	26,0	936,0	1612,0	16

11318	3 G 35	25,2	1008,0	1590,0	2
11319	4 G 35	28,0	1344,0	2200,0	2
11320	5 G 35	31,0	1680,0	2693,0	2
11321	3 G 50	29,5	1440,0	2571,0	1
11322	4 G 50	33,4	1920,0	3087,0	1
11323	5 G 50	37,2	2400,0	3980,0	1
11324	3 G 70	37,0	2016,0	3207,0	2/0
11325	4 G 70	41,2	2688,0	4077,0	2/0
11326	5 G 70	46,0	3360,0	5501,0	2/0
11327	3 G 95	41,0	2736,0	4708,0	3/0
11328	4 G 95	46,0	3648,0	5590,0	3/0
11329	5 G 95	50,5	4560,0	6972,0	3/0
11330	3 G 120	45,7	3456,0	5515,0	4/0
11331	4 G 120	50,3	4608,0	7100,0	4/0

Dimensions and specifications may be changed without prior notice. (RA03)

Quality assurance inspections with the aid of a stereo microscope at our Windsbach factory.

