

JZ-500 HMH-C flexible control cable, halogen-free, extremely fire resistant, oil resistant¹⁾, Cu-screened, EMC-preferred type, meter marking



A

Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.	Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
11346	5 x 0,75	7,4	71,0	95,0	18	11781	2 G 6	11,5	173,0	270,0	10
11682	7 G 0,75	8,6	91,0	130,0	18	11782	3 G 6	12,4	240,0	328,0	10
11347	7 x 0,75	8,6	91,0	130,0	18	11783	4 G 6	13,8	305,0	416,0	10
11685	12 G 0,75	10,4	142,0	203,0	18	11784	5 G 6	15,7	439,0	510,0	10
11687	18 G 0,75	12,4	212,0	290,0	18	11785	7 G 6	16,6	505,0	670,0	10
11689	25 G 0,75	14,8	281,0	413,0	18						
11700	2 x 1	6,4	50,0	66,0	17	11786	2 x 10	14,9	255,0	420,0	8
11701	3 G 1	6,7	60,0	80,0	17	11787	3 G 10	15,9	350,0	495,0	8
11348	3 x 1	6,7	60,0	80,0	17	11788	4 G 10	17,8	535,0	785,0	8
11702	4 G 1	7,3	71,0	100,0	17	11789	5 G 10	19,6	592,0	855,0	8
11349	4 x 1	7,3	71,0	100,0	17	11790	7 G 10	21,6	810,0	1308,0	8
11703	5 G 1	7,8	88,0	130,0	17						
11704	7 G 1	9,1	111,0	160,0	17	11793	4 G 16	20,8	740,0	882,0	6
11707	12 G 1	11,2	184,0	260,0	17	11794	5 G 16	22,9	895,0	1293,0	6
11709	18 G 1	13,2	260,0	382,0	17	11812	7 G 16	25,0	1282,0	2149,0	6
11711	25 G 1	15,8	349,0	540,0	17						
11722	2 x 1,5	6,6	63,0	88,0	16	11795	3 G 25	23,2	1070,0	1432,0	4
11723	3 G 1,5	6,9	80,0	100,0	16	11796	4 G 25	26,2	1140,0	1911,0	4
11350	3 x 1,5	6,9	80,0	100,0	16	11797	5 G 25	29,4	1380,0	2414,0	4
11724	4 G 1,5	7,5	97,0	125,0	16						
11725	5 G 1,5	8,4	119,0	158,0	16	11798	3 G 35	25,7	1240,0	1914,0	2
11726	7 G 1,5	10,0	147,0	210,0	16	11799	4 G 35	30,4	1576,0	2542,0	2
11729	12 G 1,5	12,1	267,0	340,0	16	11800	5 G 35	33,8	1930,0	3180,0	2
11731	18 G 1,5	14,6	374,0	480,0	16						
11733	25 G 1,5	17,6	526,0	702,0	16	11801	3 G 50	30,0	1675,0	3080,0	1
						11802	4 G 50	34,6	2155,0	3550,0	1
11744	2 x 2,5	8,3	96,0	132,0	14	11803	5 G 50	38,8	2794,0	4753,0	1
11745	3 G 2,5	9,0	144,0	168,0	14						
11746	4 G 2,5	9,8	148,0	195,0	14	11804	3 G 70	37,6	2288,0	3840,0	2/0
11747	5 G 2,5	10,9	181,0	222,0	14	11805	4 G 70	41,3	3120,0	4939,0	2/0
11748	7 G 2,5	12,9	255,0	345,0	14	11806	5 G 70	46,1	3705,0	6572,0	2/0
11751	12 G 2,5	15,9	441,0	572,0	14						
						11807	3 G 95	41,2	3010,0	5651,0	3/0
11766	2 x 4	9,8	120,0	184,0	12	11808	4 G 95	46,2	4043,0	6690,0	3/0
11768	3 G 4	10,6	174,0	238,0	12	11809	5 G 95	51,2	5026,0	8370,0	3/0
11769	4 G 4	11,5	230,0	305,0	12						
11770	5 G 4	12,7	273,0	388,0	12	11810	3 G 120	46,5	3812,0	6342,0	4/0
11771	7 G 4	14,0	316,0	504,0	12	11811	4 G 120	51,0	5069,0	8453,0	4/0

Dimensions and specifications may be changed without prior notice. (RA03)

Our Service on the Internet

The screenshot shows the HELUKABEL website interface. At the top, there is a navigation menu with links for Download centre, Logistic centre, Company, Products, Quality, News, Contact, Service, Opinion, and Imprint. A search bar is located on the right. Below the menu, there is a 'Photovoltaic system' section with an image of solar panels and text describing a range of wires and accessories for solar plants. A 'Welcome to HELUKABEL' message is visible, along with a list of services: News, Fairs, Job posting, Special offer's, and Press Contact. A world map is shown in the bottom right corner with a 'please select...' dropdown menu.

News

Here you will find current information on the subjects of:
 News – fairs – job posting – special offers – press contact.
 Click on the topic to get more information.

www.helukabel.de