

JB-500 HMMH-C flexible control cable, coloured core, halogen-free, screened, extremely fire resistant, oil resistant¹⁾, EMC-preferred type, meter marking



A

Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.	Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
11953	4 G 10	17,9	535,0	804,0	8	11959	4 G 35	30,6	1576,0	2540,0	2
11954	5 G 10	19,9	592,0	942,0	8	11960	5 G 35	34,0	1930,0	3260,0	2
11955	4 G 16	21,0	740,0	1190,0	6	11961	4 G 50	35,0	2155,0	3668,0	1
11956	5 G 16	23,1	895,0	1370,0	6	11962	4 G 70	41,5	3120,0	5076,0	2/0
11957	4 G 25	26,7	1140,0	1968,0	4	11963	4 G 95	46,8	4043,0	6807,0	3/0
11958	5 G 25	29,7	1380,0	2514,0	4	11964	4 G 120	51,9	5069,0	8612,0	4/0

Dimensions and specifications may be changed without prior notice. (RA03)

Insulating, shrinking, braided and temperature protection tubes

- Braided hoses
- High temperature protection
- Insulation tubes
- Heat-shrink tubes
- End caps



You can find insulating, shrinking, braided and temperature protection tubes in our catalogue Cable Accessories. Request it now at www.helukabel.de