

BIOFLEX-500®-JZ-C Bio-fuel resistant, abrasion resistant, recyclable environment friendly, bio-oil resistant¹⁾, Cu-screened, EMC-preferred type, meter marking

A

Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.	Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
25747	3 G 6	15,2	245,0	453,0	10	25755	4 G 25	30,6	1169,0	1894,0	4
25748	4 G 6	17,0	316,0	560,0	10	25756	4 G 35	36,9	1680,0	2395,0	2
25749	5 G 6	18,6	442,0	700,0	10	25757	4 G 50	41,3	2370,0	3312,0	1
25750	3 G 10	19,5	367,0	750,0	8	25758	4 G 70	48,8	3257,0	4605,0	2/0
25751	4 G 10	21,5	549,0	1023,0	8	25759	4 G 95	61,8	4060,0	6055,0	3/0
25752	5 G 10	23,9	604,0	1114,0	8	25760	4 G 120	65,7	5231,0	7318,0	4/0
25753	4 G 16	24,6	807,0	1385,0	6						
25754	5 G 16	27,3	940,0	1550,0	6						

Dimensions and specifications may be changed without prior notice. (RA05)

Drag Chain Systems

- Open chains
- Closed chains
- Accessories
- Installation instructions
- Selection tables



You can find drag chain systems in our catalogue Cable Accessories. Request it now at www.helukabel.de

