

Contents

Description	Page
TRONIC (LiYY), flexible, colour coded to DIN 47100, meter marking	B 4
PAAR-TRONIC, flexible, unscreened, colour coded to DIN 47100, meter marking	B 6
DATAFLAMM, halogen-free, meter marking	B 8
TRONIC-CY (LiY-CY), flexible, Cu-screened, colour coded to DIN 47100, EMC-preferred type, meter marking	B 9
PAAR-TRONIC-CY, flexible, Cu-unscreened, colour coded to DIN 47100, EMC-preferred type, meter marking	B 11
PAAR-CY-OZ, flexible, Cu-screened, EMC-preferred type, meter marking	B 13
PAAR-TRONIC-CY-CY (LiYCY-CY), EMC-preferred type, meter marking	B 14
PAAR-TRONIC-Li-2YCY / -Li-2YCYV, PE-insulated, low capacitance, Termi-Point®, EMC-preferred type, meter marking	B 16
LiFYCY, high flexible, paired, screened, EMC-preferred type, meter marking	B 17
TRONIC 1-CY, each core individually screened, EMC-preferred type, meter marking	B 18
TRONIC 2-CY, 2 cores screened, meter marking	B 19
LiY-TPC-Y, pairs screened, EMC-preferred type, meter marking	B 20
DATAPUR-C, EMC-preferred type, Cu-screened, PUR-outer jacket, meter marking	B 21
DATAFLAMM-C, EMC-preferred type, halogen-free, screened, meter marking	B 22
DATAFLAMM-C-PAAR, EMC-preferred type, halogen-free, screened, meter marking	B 23
EDV-PiMF-CY, PE-insulated, low capacitance, EMC-preferred type, meter marking	B 24
RD-Y(St)Y, Instrumentation Cable for Maxi-Term-Point®-connection, meter marking	B 25
RD-Y(St)YV / RD-Y(St)YY, reinforced (double) outer jacket, instrumentation cable, Maxi-Termi-Point®, meter marking	B 26
RE-2Y(St)YV, instrumentation cable, reinforced outer jacket, meter marking	B 27
RE-2Y(St)YV PiMF, Instrumentation cable, pairs screened, reinforced outer jacket, meter marking	B 28
J-2Y(St)Y, St III Bd 16 Mbits/s (Kat. 3) ISDN/EDV (Z = 100 Ohm), meter marking	B 29
JE-Y(St)Y, Bd Si Industry-Elektronik Cable according to DIN VDE 0815	B 30
JE-LiYCY, Bd Si Industry-Elektronik Cable according to DIN VDE 0815	B 31
JE-LiHCH, Bd industry electronic cable, halogen-free, according to VDE 0815	B 32
RD-H(ST)H, Bd instrumentation cable, halogen-free	B 33