

JZ-HF flexible, number coded, control cable for drag chains, meter marking



marking

Part No.	No. cores x cross-sec. mm²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
15037	2 x 1	5,7	19,0	65,0	17
15038	3 G 1	6,0	29,0	84,0	17
15039	4 G 1	6,8	38,0	113,0	17
15040	5 G 1	7,4	48,0	137,0	17
15041	7 G 1	8,8	67,0	192,0	17
15042	10 G 1	10,7	96,0	251,0	17
15043	12 G 1	10,8	115,0	295,0	17
15044	14 G 1	11,6	134,0	337,0	17
15045	16 G 1	12,2	154,0	379,0	17
15046	18 G 1	13,0	173,0	420,0	17
15047	20 G 1	13,6	192,0	480,0	17
15048	25 G 1	15,8	240,0	600,0	17
15049	30 G 1	16,4	288,0	695,0	17
15050	34 G 1	17,8	326,0	777,0	17
15051	36 G 1	17,8	346,0	825,0	17
15052	41 G 1	19,3	403,0	926,0	17
15214	42 G 1	19,3	403,0	948,0	17
15053	50 G 1	21,2	480,0	1092,0	17
15092	61 G 1	23,7	586,0	1204,0	17
15054	65 G 1	24,4	624,0	1400,0	17
15055	2 x 1,5	6,4	29,0	91,0	16
15056	3 G 1,5	6,8	43,0	117,0	16
15057	4 G 1,5	7,4	58,0	147,0	16
15058	5 G 1,5	8,3	72,0	181,0	16
15059	7 G 1,5	9,9	101,0	273,0	16
15060	10 G 1,5	11,9	144,0	344,0	16
15061	12 G 1,5	12,1	173,0	391,0	16
15062	14 G 1,5	12,9	202,0	457,0	16
15063	16 G 1,5	13,6	230,0	525,0	16
15064	18 G 1,5	14,5	259,0	590,0	16
15065	20 G 1,5	15,2	288,0	650,0	16
15066	25 G 1,5	17,8	360,0	801,0	16
15067	30 G 1,5	18,2	432,0	958,0	16
15068	34 G 1,5	19,7	490,0	1084,0	16
15069	36 G 1,5	19,7	518,0	1135,0	16
15070	42 G 1,5	21,5	605,0	1290,0	16
15071	50 G 1,5	23,7	720,0	1521,0	16
15072	60 G 1,5	25,3	864,0	1885,0	16
15215	61 G 1,5	26,2	878,0	1916,0	16
15216	65 G 1,5	27,2	936,0	1994,0	16

Part No.	No. cores x cross-sec. mm²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
15073	2 x 2,5	7,7	43,0	130,0	14
15074	3 G 2,5	8,4	72,0	160,0	14
15075	4 G 2,5	9,1	96,0	200,0	14
15076	5 G 2,5	10,2	120,0	268,0	14
15077	7 G 2,5	12,2	168,0	357,0	14
15078	10 G 2,5	15,0	240,0	486,0	14
15079	12 G 2,5	15,2	288,0	572,0	14
15080	14 G 2,5	16,1	336,0	612,0	14
15081	16 G 2,5	17,2	384,0	702,0	14
15082	18 G 2,5	18,1	432,0	800,0	14
15083	20 G 2,5	19,2	480,0	920,0	14
15084	25 G 2,5	22,5	600,0	1100,0	14
15085	30 G 2,5	23,5	720,0	1400,0	14
15086	34 G 2,5	25,2	816,0	1500,0	14
15087	36 G 2,5	25,2	864,0	1600,0	14
15088	42 G 2,5	27,4	1008,0	1800,0	14
15089	50 G 2,5	30,0	1200,0	2100,0	14
15142	3 G 4	10,4	115,0	221,0	12
15143	4 G 4	11,4	154,0	260,0	12
15144	5 G 4	12,7	192,0	318,0	12
15145	4 G 6	13,3	230,0	392,0	10
15146	5 G 6	14,5	288,0	481,0	10
15147	4 G 10	17,7	384,0	642,0	8
15148	5 G 10	19,7	480,0	780,0	8
15149	4 G 16	20,8	614,0	926,0	6
15150	5 G 16	23,5	768,0	1155,0	6

Dimensions and specifications may be changed without prior notice. (RC01)

HELUKABEL GMBH						
Schleppketten-Testergebnis						
Type:	JZ-HF / -CY					
Art. Nr	Aderzahl x Nennquerschnitt mm	Außendurchmesser mm	geschlmt	Maximal- biegeradius	Min. biegeradius	Min. Biegeradius
15023	7G0,75	8,30	nein	7,5d	240	1.800,00
15005	7G0,5	7,50	nein	7,5d	240	1.800,00
15041	7G1	8,60	nein	7,5d	240	1.800,00
15058	5G1,5	9,30	nein	7,5d	240	1.800,00
15006	10G0,5	9,10	nein	10d	240	1.800,00
15075	4G2,5	15,40	ja	10d	240	1.800,00
15967	18G1	13,10	ja	10d	240	1.800,00
15986	14G0,75	13,10	ja	10d	240	1.800,00
15986	12G1	14,40	ja	10d	240	1.800,00
15966	7G2,5	12,70	ja	10d	240	1.800,00
15928	5G2,5	14,50	nein	7,5d	240	1.800,00

To be able to provide information on the service life and in line with our certification to DIN EN ISO 9001:2000, we document the realistic testing of our cables suitable for use in drag chains.