

JZ-HF-CY high flexible, screened control cable for drag chains, EMC-preferred type, meter marking



| Part No. | No. cores x cross-sec. mm ² | Outer ø app. mm | Cop. weight kg / km | Weight app. kg / km | AWG-No. |
|----------|--|-----------------|---------------------|---------------------|---------|
| 15961 | 2 x 1 | 8,1 | 56,0 | 115,0 | 17 |
| 15962 | 3 G 1 | 8,4 | 66,0 | 142,0 | 17 |
| 15963 | 4 G 1 | 9,0 | 80,0 | 196,0 | 17 |
| 15964 | 5 G 1 | 9,8 | 114,0 | 271,0 | 17 |
| 15965 | 7 G 1 | 11,2 | 129,0 | 307,0 | 17 |
| 15966 | 12 G 1 | 13,4 | 235,0 | 474,0 | 17 |
| 15967 | 18 G 1 | 15,7 | 309,0 | 622,0 | 17 |
| 15968 | 25 G 1 | 19,0 | 417,0 | 828,0 | 17 |
| 15969 | 34 G 1 | 21,0 | 519,0 | 1049,0 | 17 |
| 15970 | 41 G 1 | 22,7 | 635,0 | 1257,0 | 17 |
| 15971 | 50 G 1 | 24,5 | 735,0 | 1437,0 | 17 |
| 15972 | 65 G 1 | 27,7 | 932,0 | 1823,0 | 17 |
| 15976 | 2 x 1,5 | 8,6 | 75,0 | 170,0 | 16 |
| 15977 | 3 G 1,5 | 9,0 | 90,0 | 203,0 | 16 |
| 15978 | 4 G 1,5 | 9,8 | 112,0 | 243,0 | 16 |
| 15979 | 5 G 1,5 | 10,5 | 132,0 | 288,0 | 16 |
| 15980 | 7 G 1,5 | 12,5 | 218,0 | 403,0 | 16 |
| 15981 | 12 G 1,5 | 14,8 | 309,0 | 592,0 | 16 |
| 15982 | 18 G 1,5 | 17,3 | 481,0 | 844,0 | 16 |
| 15983 | 25 G 1,5 | 21,0 | 584,0 | 1155,0 | 16 |
| 15152 | 41 G 1,5 | 24,8 | 867,0 | 1227,0 | 16 |
| 15153 | 50 G 1,5 | 27,3 | 970,0 | 1445,0 | 16 |
| 15154 | 61 G 1,5 | 29,8 | 1028,0 | 1724,0 | 16 |

| Part No. | No. cores x cross-sec. mm ² | Outer ø app. mm | Cop. weight kg / km | Weight app. kg / km | AWG-No. |
|----------|--|-----------------|---------------------|---------------------|---------|
| 15925 | 3 G 2,5 | 10,8 | 140,0 | 215,0 | 14 |
| 15926 | 4 G 2,5 | 11,5 | 169,0 | 264,0 | 14 |
| 15927 | 5 G 2,5 | 12,9 | 194,0 | 344,0 | 14 |
| 15928 | 7 G 2,5 | 15,1 | 234,0 | 410,0 | 14 |
| 15929 | 12 G 2,5 | 18,4 | 364,0 | 721,0 | 14 |
| 15155 | 3 G 4 | 13,0 | 178,0 | 292,0 | 12 |
| 15156 | 4 G 4 | 14,2 | 222,0 | 372,0 | 12 |
| 15157 | 5 G 4 | 15,6 | 328,0 | 448,0 | 12 |
| 15158 | 4 G 6 | 16,0 | 305,0 | 526,0 | 10 |
| 15159 | 5 G 6 | 17,5 | 441,0 | 632,0 | 10 |
| 15160 | 4 G 10 | 21,2 | 485,0 | 838,0 | 8 |
| 15161 | 5 G 10 | 23,2 | 610,0 | 998,0 | 8 |
| 15162 | 4 G 16 | 24,1 | 840,0 | 1225,0 | 6 |
| 15163 | 5 G 16 | 27,0 | 1050,0 | 1560,0 | 6 |

Dimensions and specifications may be changed without prior notice. (RC01)

Our Service on the Internet

The screenshot shows the HELUKABEL website interface. At the top, there are navigation links: Download centre, Logistic centre, Company, Products, Quality, News, Contact, Service, Opinion, and Imprint. A search bar is visible on the right. Below the navigation, a breadcrumb trail reads: You are here: Home > Service > HELU - Newsletter. A dropdown menu is open under 'Service', listing: Helis, Metal quotes, Download centre, Certificate of compliance, Catalogue request, HELU - Newsletter (highlighted), ONLINE - inquiry, and Inquiry form for spiral cables. On the left, a 'Service' sidebar lists: Helis, Metal quotes, Download centre, Certificate of compliance, Catalogue request, HELU - Newsletter, and ONLINE - inquiry. The main content area is titled 'HELU - Newsletter' and contains the text: 'Use our HELU-Newsletter, to receive actual special-price many things more.' Below this is a 'Newsletter-subscription:' section with an 'Email-address:' field and a submit button. On the right, there is a 'HELUKABEL world-wide' section with a world map and a 'please select...' dropdown menu.

HELU Newsletter

Take advantage of our HELU Newsletter service:
It's free and without obligation. We report on HELUKABEL's®
broad product spectrum, such as new products, trade fairs,
industry news and much more.

www.helukabel.de