

MULTIFLEX 512®-PUR special cable for drag chains,

halogen-free, meter marking



Part No.	No. cores x cross-sec. mm²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
22523	2 x 1	6,9	19,2	55,0	17
22524	3 G 1	7,4	29,0	70,0	17
22525	4 G 1	8,0	38,0	86,0	17
22526	5 G 1	8,7	48,0	102,0	17
22527	7 G 1	10,2	67,0	143,0	17
22528	12 G 1	12,6	115,0	225,0	17
22529	18 G 1	14,8	173,0	334,0	17
22530	20 G 1	15,8	192,0	370,0	17
22531	25 G 1	18,1	240,0	460,0	17
22532	30 G 1	18,5	288,0	530,0	17
22533	36 G 1	20,1	346,0	625,0	17
22878	41 G 1	22,0	410,0	779,0	17
22879	50 G 1	24,0	498,0	953,0	17
22880	65 G 1	27,2	650,0	1205,0	17
22534	2 x 1,5	7,6	29,0	70,0	16
22535	3 G 1,5	8,1	43,0	90,0	16
22536	4 G 1,5	8,7	58,0	106,0	16
22537	5 G 1,5	9,7	72,0	145,0	16
22538	7 G 1,5	11,3	101,0	205,0	16
22539	12 G 1,5	13,8	173,0	320,0	16
22540	18 G 1,5	16,3	259,0	465,0	16
22541	20 G 1,5	17,3	288,0	510,0	16
22542	25 G 1,5	19,8	360,0	650,0	16
22543	30 G 1,5	20,3	432,0	750,0	16
22544	36 G 1,5	22,2	518,0	880,0	16
22881	42 G 1,5	24,0	628,0	1209,0	16
22882	50 G 1,5	26,2	749,0	1449,0	16
22883	61 G 1,5	28,9	912,0	1712,0	16

Part No.	No. cores x cross-sec. mm²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
22545	2 x 2,5	9,2	48,0	115,0	14
22546	3 G 2,5	9,7	72,0	162,0	14
22547	4 G 2,5	10,5	96,0	196,0	14
22548	5 G 2,5	11,6	120,0	230,0	14
22549	7 G 2,5	13,8	168,0	312,0	14
22550	12 G 2,5	16,9	288,0	532,0	14
22551	18 G 2,5	20,0	432,0	762,0	14
22552	20 G 2,5	21,2	480,0	858,0	14
22553	25 G 2,5	24,4	600,0	998,0	14
22554	4 G 4	13,2	154,0	283,0	12
22555	5 G 4	14,6	192,0	349,0	12
22556	7 G 4	17,6	269,0	498,0	12
22557	4 G 6	14,4	230,0	432,0	10
22558	5 G 6	15,9	288,0	529,0	10
22559	7 G 6	19,2	403,0	782,0	10
22560	4 G 10	18,4	384,0	685,0	8
22561	5 G 10	20,7	480,0	817,0	8
22562	7 G 10	24,7	672,0	1023,0	8
22563	4 G 16	21,3	614,0	1042,0	6
22564	5 G 16	23,8	768,0	1292,0	6
22565	7 G 16	28,6	1075,0	1709,0	6

Dimensions and specifications may be changed without prior notice. (RC02)

HELUKABEL GMBH MULTIFLEX 512 PUR / C - PUR						
Art. Nr.	Aderzahl x Nennquerschnitt mm	Außerdurchmesser mm	geschlitt	Mindestbiegeradius	PA-Nr.	Typische Eigenschaften
22516	7G0,5	8,10	nein	5d	337	1.288.712
22519	20G,75	13,50	nein	5d	2878	1.288.712
22527	18G0,5	11,50	nein	5d	2742	1.288.712
22527	7G1	10,20	nein	5d	2792	1.288.712
22518	18G70,5	12,90	nein	5d	2884	1.288.712
22550	12G2,5	16,90	nein	5d	4171	1.288.712
22555	25G2,5	24,40	nein	5d	4421	1.288.712
22559	7G6	19,20	nein	5d	4398	1.288.712
22579	25G0,5	17,00	ja	7,5d	2817	1.288.712
22588	18G0,75	16,30	ja	7,5d	4398	1.288.712
22578	20G0,5	15,40	ja	7,5d	2377	1.288.712
22573	4G0,5	9,30	ja	7,5d	2318	1.411.288

To be able to provide information on the service life and in line with our certification to DIN EN ISO 9001:2000, we document the realistic testing of our cables suitable for use in drag chains.