

MULTISPEED® 500-TPE high flexible, safety against high bending

in drag chain systems, low torsion, halogen-free, meter marking



Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
24209	2 x 1	5,2	19,2	50,0	17
24210	3 G 1	5,4	29,0	60,0	17
24211	4 G 1	5,9	38,0	74,0	17
24212	5 G 1	6,7	48,0	86,0	17
24213	7 G 1	11,0	67,0	114,0	17
24214	12 G 1	11,8	115,0	210,0	17
24215	18 G 1	14,6	173,0	291,0	17
24216	25 G 1	16,5	240,0	380,0	17
24043	41 G 1	22,0	394,0	510,0	2
24217	3 G 1,5	6,4	43,0	84,0	16
24218	4 G 1,5	7,0	58,0	108,0	16
24219	5 G 1,5	7,8	72,0	126,0	16
24220	7 G 1,5	13,0	101,0	169,0	16
24221	12 G 1,5	14,1	173,0	299,0	16
24222	18 G 1,5	17,1	259,0	460,0	16
24223	25 G 1,5	19,3	360,0	640,0	16

Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
24224	4 G 2,5	8,8	96,0	179,0	14
24225	5 G 2,5	9,8	120,0	230,0	14
24226	7 G 2,5	16,1	168,0	294,0	14
24227	12 G 2,5	17,5	288,0	510,0	14
24228	18 G 2,5	21,4	432,0	722,0	14
24229	25 G 2,5	24,0	600,0	950,0	14
24230	4 G 4	10,3	154,0	197,0	12
24231	4 G 6	11,9	231,0	320,0	10
24232	5 G 6	13,4	289,0	394,0	10
24233	4 G 10	14,7	387,0	520,0	8
24234	4 G 16	20,0	517,0	784,0	6
24235	4 G 35	24,9	1344,0	1711,0	2

Dimensions and specifications may be changed without prior notice. (RC02)

Conduits

Corrugated tubes

- for standard applications
- for larger sizes
- scissile corrugated tubes
- conduit glands

High flexible conduits

- plastic conduits with spiral spring
- metal conduits
- conduits glands

Conduit for heavy mechanical duty

- metal conduits with plastic sheat
- plastic conduits
- conduits glands for metal conduits



You can find conduits in our catalogue **Cable Accessories**.
Request it now at www.helukabel.de