



## Technical data

- Special PVC control cable with oil resistant outer sheath to DIN VDE 0281 part 13, HD 21.13 S1 and to UL-Style 2587
- **Temperature range**  
flexing  
-5°C to +70°C (HAR)  
-5°C to +90°C (UL+CSA)  
fixed installation  
-40°C to +70°C (HAR)  
-40°C to +90°C (UL+CSA)
- **Nominal voltage**  
U<sub>0</sub>/U 300/500 V (HAR)  
U 600 V (UL+CSA)
- **Test voltage** 3000 V
- **Breakdown voltage** min. 6000 V
- **Insulation resistance**  
min. 20 MOhm x km
- **Minimum bending radius**  
flexing 7,5x cable Ø  
fixed installation 3x cable Ø
- **Radiation resistance**  
up to 80x10<sup>6</sup> cJ/kg (up to 80 Mrad)

## Cable structure

- Bare copper, fine wire conductors to DIN VDE 0295 cl. 5, BS 6360 cl. 5 and IEC 60228 cl. 5
- Special PVC core insulation T11, to DIN VDE 0281 part 1, HD 21.1S2 and class 43 to UL-Std. 1581
- Black cores with white continuous numbering
- Green-yellow earth core in the outer layer
- Cores stranded in layers with optimal lay-length
- Special PVC outer sheath TM5 oil resistant, to DIN VDE 0281 part 1, HD 21.1 S4 and class 43 to UL-Std. 1581
- Colour grey (RAL 7001)
- with meter marking, change-over in 2009

## Properties

- Oil resistant as per HD/EN 60811-2-1, UL 1581 part 50.182
- PVC self-extinguishing and flame retardant according to VDE 0482-332-1-2, DIN EN 60332-1-2/ IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers

## Note

- G = with green-yellow earth core; x = without green-yellow earth core (OZ).
- AWG sizes are approximate equivalent values. The actual cross-section is in mm<sup>2</sup>.
- The following amendments in the cable designation result from the new DIN VDE 0281 part 13 / harmonised in accordance with HD 21.13S1: NYSLYÖ-J (new: H05VV5-F) and NYSLYCÖ-J (new: H05VVC4V5-K). SEV-approval is no longer applicable as a result of the harmonisation.
- **screened analogue type:**  
**JZ-603-CY** see page N 21

## Application

UL-CSA-HAR approved cables offer any company exporting anywhere in the world, primarily designed for exporters, used in machine tools, control systems, assembly lines and other industrial equipment. These cables are suitable for flexible use for medium mechanical stresses with free movements in dry, moist and wet rooms but not for open air.

CE= The product is conformed with the EC Low-Voltage Directive 2006/95/EG.

Part No.	No. cores x cross-sec. mm <sup>2</sup>	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	Part No.	No. cores x cross-sec. mm <sup>2</sup>	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
83704	2 x 0,5	20	5,7	9,6	52,0	83677	18 G 1	18	14,7	173,0	405,0
83650	3 G 0,5	20	6,1	14,0	63,0	83678	25 G 1	18	18,0	240,0	570,0
83651	4 G 0,5	20	6,7	19,0	69,0	83679	34 G 1	18	20,3	326,0	742,0
83652	5 G 0,5	20	7,3	24,0	87,0	83680	41 G 1	18	22,4	394,0	885,0
83653	7 G 0,5	20	8,8	34,0	119,0	83681	50 G 1	18	24,3	480,0	1071,0
83654	12 G 0,5	20	11,1	58,0	198,0	83682	61 G 1	18	26,8	586,0	1265,0
83655	18 G 0,5	20	12,9	86,0	266,0						
83656	25 G 0,5	20	16,0	120,0	380,0	83707	2 x 1,5	16	7,4	28,8	91,0
83657	34 G 0,5	20	17,7	163,0	508,0	83683	3 G 1,5	16	8,0	43,0	110,0
83658	41 G 0,5	20	19,5	197,0	594,0	83684	4 G 1,5	16	8,7	58,0	141,0
83659	50 G 0,5	20	21,3	240,0	715,0	83685	5 G 1,5	16	9,8	72,0	167,0
83660	61 G 0,5	20	23,8	293,0	840,0	83686	7 G 1,5	16	11,9	101,0	225,0
						83687	12 G 1,5	16	14,5	173,0	361,0
83705	2 x 0,75	19	6,0	14,4	66,0	83688	18 G 1,5	16	17,4	259,0	518,0
83661	3 G 0,75	19	6,5	22,0	76,0	83689	25 G 1,5	16	21,3	360,0	730,0
83662	4 G 0,75	19	7,1	29,0	85,0	83690	34 G 1,5	16	24,1	490,0	945,0
83663	5 G 0,75	19	7,9	36,0	113,0	83691	41 G 1,5	16	26,2	591,0	1135,0
83664	7 G 0,75	19	9,5	50,0	144,0	83692	50 G 1,5	16	28,8	720,0	1381,0
83665	12 G 0,75	19	11,6	86,0	245,0	83693	61 G 1,5	16	31,5	878,0	1640,0
83666	18 G 0,75	19	13,9	130,0	327,0						
83667	25 G 0,75	19	17,1	180,0	466,0	83708	2 x 2,5	14	9,2	48,0	125,0
83668	34 G 0,75	19	19,1	245,0	626,0	83694	3 G 2,5	14	9,9	72,0	169,0
83669	41 G 0,75	19	20,9	296,0	747,0	83695	4 G 2,5	14	11,0	96,0	209,0
83670	50 G 0,75	19	23,0	360,0	896,0	83696	5 G 2,5	14	12,0	120,0	256,0
83671	61 G 0,75	19	25,3	439,0	1070,0	83697	7 G 2,5	14	14,6	168,0	340,0
						83698	12 G 2,5	14	18,1	288,0	579,0
83706	2 x 1	18	6,3	19,2	70,0	83699	18 G 2,5	14	22,1	432,0	851,0
83672	3 G 1	18	6,8	29,0	88,0	83700	25 G 2,5	14	26,5	600,0	1175,0
83673	4 G 1	18	7,5	39,0	99,0	83701	34 G 2,5	14	29,9	816,0	1529,0
83674	5 G 1	18	8,4	48,0	132,0	83702	50 G 2,5	14	35,2	1200,0	2290,0
83675	7 G 1	18	10,0	67,0	170,0	83703	61 G 2,5	14	38,4	1464,0	2724,0
83676	12 G 1	18	12,5	115,0	285,0						

Dimensions and specifications may be changed without prior notice. (RN01)