

JZ-600 UL/CSA flexible, number coded, 0,6/1kV, meter marking



Part No. Jacket colour	No. cores x cross-sec. mm ²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	Part No. Jacket colour	No. cores x cross-sec. mm ²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
11844	12 G 1,5	16	16,6	173,0	370,0	11909	12 G 1,5	16	16,6	173,0	370,0
11845	18 G 1,5	16	19,7	259,0	520,0	11910	18 G 1,5	16	19,7	259,0	520,0
11846	25 G 1,5	16	23,9	360,0	730,0	11911	25 G 1,5	16	23,9	360,0	730,0
11847	2 x 2,5	14	9,4	48,0	160,0	11912	2 x 2,5	14	9,4	48,0	160,0
11848	3 G 2,5	14	9,9	72,0	175,0	11913	3 G 2,5	14	9,9	72,0	175,0
11849	4 G 2,5	14	11,1	96,0	203,0	11914	4 G 2,5	14	11,1	96,0	203,0
11850	5 G 2,5	14	12,4	120,0	251,0	11915	5 G 2,5	14	12,4	120,0	251,0
11851	7 G 2,5	14	15,0	168,0	330,0	11916	7 G 2,5	14	15,0	168,0	330,0
11852	12 G 2,5	14	18,4	288,0	553,0	11917	12 G 2,5	14	18,4	288,0	553,0
11853	18 G 2,5	14	22,0	432,0	795,0	11918	18 G 2,5	14	22,0	432,0	795,0
11854	25 G 2,5	14	26,9	600,0	1110,0	11919	25 G 2,5	14	26,9	600,0	1110,0
11855	2 x 4	12	11,4	77,0	180,0	11920	2 x 4	12	11,4	77,0	180,0
11856	3 G 4	12	12,3	115,0	230,0	11921	3 G 4	12	12,3	115,0	230,0
11857	4 G 4	12	13,8	154,0	310,0	11922	4 G 4	12	13,8	154,0	310,0
11858	5 G 4	12	15,3	192,0	410,0	11923	5 G 4	12	15,3	192,0	410,0
11859	7 G 4	12	16,8	269,0	540,0	11924	7 G 4	12	16,8	269,0	540,0
11860	12 G 4	12	22,9	461,0	860,0	11925	12 G 4	12	22,9	461,0	860,0
11861	3 G 6	10	14,1	173,0	370,0	11926	3 G 6	10	14,1	173,0	370,0
11862	4 G 6	10	15,6	230,0	430,0	11927	4 G 6	10	15,6	230,0	430,0
11863	5 G 6	10	17,3	288,0	650,0	11928	5 G 6	10	17,3	288,0	650,0
11864	7 G 6	10	19,3	403,0	860,0	11929	7 G 6	10	19,3	403,0	860,0
11865	3 G 10	8	16,5	288,0	660,0	11930	3 G 10	8	16,5	288,0	660,0
11866	4 G 10	8	18,4	384,0	790,0	11931	4 G 10	8	18,4	384,0	790,0
11867	5 G 10	8	20,5	480,0	960,0	11932	5 G 10	8	20,5	480,0	960,0
11868	7 G 10	8	22,5	672,0	1300,0	11933	7 G 10	8	22,5	672,0	1300,0
11869	3 G 16	6	19,6	461,0	760,0	11934	3 G 16	6	19,6	461,0	760,0
11870	4 G 16	6	21,7	614,0	1100,0	11935	4 G 16	6	21,7	614,0	1100,0
11871	5 G 16	6	24,2	768,0	1600,0	11936	5 G 16	6	24,2	768,0	1600,0
11872	7 G 16	6	25,7	1075,0	1890,0	11937	7 G 16	6	25,7	1075,0	1890,0
11873	3 G 25	4	24,0	720,0	1450,0	11938	3 G 25	4	24,0	720,0	1450,0
11874	4 G 25	4	26,9	960,0	1600,0	11939	4 G 25	4	26,9	960,0	1600,0
11875	5 G 25	4	29,3	1200,0	2050,0	11940	5 G 25	4	29,3	1200,0	2050,0
11876	7 G 25	4	32,6	1680,0	2900,0	11941	7 G 25	4	32,6	1680,0	2900,0

Dimensions and specifications may be changed without prior notice. (RN01)

N

Our Service on the Internet

The screenshot shows the HELUKABEL website interface. At the top, there are navigation links: Download centre, Logistic centre, Company, Products, Quality, News, Contact, Service, Opinion, and Imprint. A search bar is located on the right. Below the navigation, a breadcrumb trail reads: You are here: Home > Service > HELU - Newsletter. A dropdown menu for 'Service' is open, listing options like Helis, Metal quotes, Download centre, Certificate of compliance, Catalogue request, HELU - Newsletter (highlighted), ONLINE - inquiry, and Inquiry form for spiral cables. On the right, there is a 'HELUKABEL world-wide' section with a world map and a 'please select...' dropdown. In the center, the 'HELU - Newsletter' section is visible, with the text: 'Use our HELU-Newsletter, to receive actual special-prices many things more.' Below this, there is a 'Newsletter-subscription:' section with an 'Email-address:' field.

HELU Newsletter

Take advantage of our HELU Newsletter service:
It's free and without obligation. We report on HELUKABEL's®
broad product spectrum, such as new products, trade fairs,
industry news and much more.

www.helukabel.de