

JZ 604 TC TRAY CABLE

PVC power cable, exposed run,
90°C, 600V, meter marking



Part No.	No. cores x cross-sec. mm ²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
69715	3 G 16	6	21,0	461,0	651,0
69716	4 G 16	6	23,9	614,0	869,0
69717	5 G 16	6	26,3	768,0	1117,0
69718	7 G 16	6	28,8	1075,0	1364,0
69719	3 G 25	4	24,9	720,0	1090,0
69720	4 G 25	4	27,2	960,0	1421,0
69721	5 G 25	4	30,3	1200,0	1611,0
69722	7 G 25	4	33,1	1680,0	1943,0
69723	3 G 35	2	27,1	1008,0	1734,0
69724	4 G 35	2	29,8	1344,0	2011,0
69725	5 G 35	2	33,0	1680,0	2347,0
69726	3 G 50	1	33,2	1440,0	2041,0
69727	4 G 50	1	36,7	1920,0	2539,0
69728	5 G 50	1	41,5	2400,0	2894,0

Part No.	No. cores x cross-sec. mm ²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
69729	3 G 70	2/0	37,6	2016,0	2831,0
69730	4 G 70	2/0	42,0	2688,0	3494,0
69731	5 G 70	2/0	47,6	3360,0	4260,0
69732	3 G 95	3/0	41,8	2736,0	5010,0
69733	4 G 95	3/0	47,0	3648,0	6104,0
69734	5 G 95	3/0	52,5	4560,0	7891,0
69735	3 G 120	4/0	46,0	3456,0	5940,0
69736	4 G 120	4/0	51,5	4608,0	7604,0
69737	5 G 120	4/0	56,5	5760,0	8751,0

Dimensions and specifications may be changed without prior notice. (RN01)

Terminations and straight-through joints

Telephone cables
Low voltage
Medium voltage
Accessories



You can find terminations and straight-through joints in our catalogue Cable Accessories.
Request it now at www.helukabel.de