

JZ-602-C-PUR screened two approvals control cable, 80°C, 600V,

EMC-preferred type, meter marking



Part No.	No. cores x cross-sec. mm ²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
12610	3 G 25	4	30,2	920,0	1947,0
12611	4 G 25	4	33,3	1169,0	2591,0
12612	5 G 25	4	36,8	1420,0	3197,0
12613	7 G 25	4	40,6	1921,0	4530,0
12614	3 G 35	2	33,8	1250,0	2701,0
12615	4 G 35	2	37,7	1680,0	3277,0

Part No.	No. cores x cross-sec. mm ²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
12616	5 G 35	2	41,5	2020,0	4530,0
12617	4 G 50	1	41,8	2370,0	3370,0
12618	4 G 70	2/0	47,0	3257,0	4630,0
12619	4 G 95	3/0	51,0	4060,0	6114,0
12620	4 G 120	4/0	58,0	5231,0	7417,0

Dimensions and specifications may be changed without prior notice. (RN01)

Conduits

Corrugated tubes

- for standard applications
- for larger sizes
- scissile corrugated tubes
- conduit glands

High flexible conduits

- plastic conduits with spiral spring
- metal conduits
- conduits glands

Conduit for heavy mechanical duty

- metal conduits with plastic sheat
- plastic conduits
- conduits glands for metal conduits



You can find conduits in our catalogue Cable Accessories.
Request it now at www.helukabel.de