

JZ-600-YC-PUR tear and coolant resistant, 0,6/1kV, Cu-screened, EMC-preferred type, meter marking



Part No. Jacket colour	No. cores x cross-sec. mm ²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
black					
28394	2 x 1,5	16	10,7	64,0	166,0
28395	3 G 1,5	16	11,2	82,0	192,0
28396	4 G 1,5	16	12,3	99,0	246,0
28397	5 G 1,5	16	13,3	123,0	294,0
28398	7 G 1,5	16	16,0	148,0	392,0
28399	12 G 1,5	16	19,6	274,0	599,0
28400	18 G 1,5	16	23,4	386,0	817,0
28401	25 G 1,5	16	28,2	531,0	1261,0
28402	2 x 2,5	14	11,8	110,0	280,0
28403	3 G 2,5	14	12,3	148,0	301,0
28404	4 G 2,5	14	13,4	169,0	352,0
28405	5 G 2,5	14	14,9	220,0	433,0
28406	7 G 2,5	14	17,9	284,0	569,0
28407	12 G 2,5	14	21,9	470,0	864,0
28408	18 G 2,5	14	26,1	572,0	1365,0
28409	25 G 2,5	14	31,9	740,0	1997,0
28410	2 x 4	12	14,3	124,0	310,0
28411	3 G 4	12	15,1	178,0	396,0
28412	4 G 4	12	16,7	234,0	531,0
28413	5 G 4	12	18,6	284,0	704,0
28414	7 G 4	12	20,0	321,0	932,0
28415	3 G 6	10	17,0	245,0	633,0
28416	4 G 6	10	18,7	316,0	742,0
28417	5 G 6	10	20,7	442,0	1117,0
28418	3 G 10	8	19,6	367,0	1131,0
28419	4 G 10	8	21,9	549,0	1357,0
28420	5 G 10	8	24,1	604,0	1646,0
28421	3 G 16	6	23,5	653,0	1397,0
28422	4 G 16	6	26,4	807,0	1880,0
28423	5 G 16	6	28,8	940,0	2721,0

Part No. Jacket colour	No. cores x cross-sec. mm ²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
grey					
28454	2 x 1,5	16	10,7	68,0	166,0
28455	3 G 1,5	16	11,2	84,0	192,0
28456	4 G 1,5	16	12,3	104,0	246,0
28457	5 G 1,5	16	13,3	123,0	294,0
28458	7 G 1,5	16	16,0	180,0	392,0
28459	12 G 1,5	16	19,6	284,0	599,0
28460	18 G 1,5	16	23,4	390,0	817,0
28461	25 G 1,5	16	28,2	521,0	1261,0
28462	2 x 2,5	14	11,8	99,0	280,0
28463	3 G 2,5	14	12,3	124,0	301,0
28464	4 G 2,5	14	13,4	170,0	352,0
28465	5 G 2,5	14	14,9	202,0	433,0
28466	7 G 2,5	14	17,9	268,0	569,0
28467	12 G 2,5	14	21,9	423,0	864,0
28468	18 G 2,5	14	26,1	572,0	1365,0
28469	25 G 2,5	14	31,9	740,0	1997,0
28470	2 x 4	12	14,3	156,0	310,0
28471	3 G 4	12	15,1	191,0	396,0
28472	4 G 4	12	16,7	236,0	531,0
28473	5 G 4	12	18,6	303,0	704,0
28474	7 G 4	12	20,0	394,0	932,0
28475	3 G 6	10	17,0	251,0	633,0
28476	4 G 6	10	18,7	319,0	742,0
28477	5 G 6	10	20,7	421,0	1117,0
28478	3 G 10	8	19,6	371,0	1131,0
28479	4 G 10	8	21,9	576,0	1357,0
28480	5 G 10	8	24,1	620,0	1646,0
28481	3 G 16	6	23,5	540,0	1397,0
28482	4 G 16	6	26,4	807,0	1880,0
28483	5 G 16	6	28,8	1394,0	2721,0

Dimensions and specifications may be changed without prior notice. (RN01)

Our Service on the Internet

The screenshot shows the HELUKABEL website interface. At the top, there are navigation links: Download centre, Logistic centre, Company, Products, Quality, News, Contact, Service, Opinion, and Imprint. A search bar is located on the right. Below the navigation, a breadcrumb trail reads 'You are here: Home > Service > Metal quotes'. The main content area features a 'Service' sidebar with links to Helis, Metal quotes, Download centre, Certificate of compliance, Catalogue request, HELU - Newsletter, and ONLINE - inquiry. The central 'Metal quotes' section includes the text 'Including 1% procurement costs.' and a search input field. A dropdown menu is open over the 'Metal quotes' link, listing: Helis, Metal quotes, Download centre, Certificate of compliance, Catalogue request, HELU - Newsletter, ONLINE - inquiry, and Inquiry form for spiral cables. At the bottom of the screenshot, there are currency selection options for 'Metal' (EUR / 100 kg) and 'US \$ / 100 kg'.

Metal quotes

On our Internet site, you will find the current metal prices for copper, brass, lead and aluminium as well as DEL prices developments and the dollar prices over the last few months.

www.helukabel.de