

MEGAFLEX® 500-C halogen-free, flame retardant, oil-resistant, UV-resistant, flexible, screened, EMC-preferred types, meter marking



Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.	Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
13516	2 x 0,75	6,1	40,0	60,0	18	13562	2 x 2,5	8,3	96,0	132,0	14
13517	3 G 0,75	6,4	52,0	68,0	18	13563	3 G 2,5	9,0	144,0	168,0	14
13518	3 x 0,75	6,4	52,0	68,0	18	13565	4 G 2,5	9,8	148,0	195,0	14
13519	4 G 0,75	6,9	60,0	78,0	18	13566	5 x 2,5	10,9	181,0	256,0	14
13520	4 x 0,75	6,9	60,0	78,0	18	13567	7 G 2,5	12,9	255,0	345,0	14
13521	5 G 0,75	7,4	71,0	95,0	18	13568	8 G 2,5	13,1	285,0	390,0	17
13522	5 x 0,75	7,4	71,0	95,0	18	13569	10 G 2,5	15,2	340,0	482,0	14
13523	7 G 0,75	8,6	91,0	130,0	18	13570	12 G 2,5	15,9	441,0	572,0	14
13524	7 x 0,75	8,6	91,0	130,0	18						
13525	8 G 0,75	9,4	110,0	145,0	18	13571	2 x 4	9,8	120,0	220,0	12
13526	10 G 0,75	10,0	137,0	180,0	18	13572	3 G 4	10,6	174,0	251,0	12
13527	12 G 0,75	10,4	142,0	203,0	18	13573	4 G 4	11,5	230,0	305,0	12
13528	16 G 0,75	11,6	200,0	275,0	18	13574	5 G 4	12,7	273,0	388,0	12
13529	18 G 0,75	12,4	212,0	290,0	18	13575	7 G 4	14,0	316,0	504,0	12
13530	20 G 0,75	12,9	238,0	320,0	18						
13531	25 G 0,75	14,8	281,0	413,0	18						
13532	2 x 1	6,4	50,0	66,0	17	13576	2 x 6	11,5	173,0	270,0	10
13533	3 G 1	6,7	60,0	80,0	17	13577	3 G 6	12,4	240,0	351,0	10
13534	3 x 1	6,7	60,0	80,0	17	13578	4 G 6	13,8	305,0	464,0	10
13535	4 G 1	7,3	71,0	100,0	17	13579	5 G 6	15,7	439,0	546,0	10
13536	4 x 1	7,3	71,0	100,0	17	13580	7 G 6	16,6	505,0	670,0	10
13537	5 G 1	7,8	88,0	130,0	17						
13538	7 G 1	9,1	111,0	160,0	17	13581	2 x 10	14,9	255,0	461,0	8
13539	8 G 1	9,9	127,0	197,0	17	13582	3 G 10	15,9	350,0	574,0	8
13540	10 G 1	10,8	150,0	232,0	17	13583	4 G 10	17,8	535,0	785,0	8
13541	12 G 1	11,2	184,0	260,0	17	13584	5 G 10	19,6	592,0	914,0	8
13542	16 G 1	12,3	209,0	346,0	17	13585	7 G 10	21,6	810,0	1308,0	8
13543	18 G 1	13,2	260,0	382,0	17						
13544	20 G 1	13,8	317,0	440,0	17	13586	2 x 16	17,2	422,0	670,0	6
13545	25 G 1	15,8	349,0	540,0	17	13587	3 G 16	19,0	585,0	911,0	6
						13588	4 G 16	20,8	740,0	1105,0	6
13546	2 x 1,5	6,6	63,0	88,0	16	13589	5 G 16	22,9	895,0	1293,0	6
13547	3 G 1,5	6,9	80,0	100,0	16	13590	7 G 16	25,0	1282,0	2149,0	6
13548	3 x 1,5	6,9	80,0	100,0	16						
13549	4 G 1,5	7,5	97,0	125,0	16	13591	4 G 25	26,2	1140,0	1911,0	4
13550	5 G 1,5	8,4	119,0	158,0	16						
13552	7 G 1,5	10,0	147,0	210,0	16	13592	4 x 35	30,4	1576,0	2542,0	2
13554	8 G 1,5	11,1	170,0	244,0	16						
13556	10 G 1,5	12,0	193,0	315,0	16	13593	4 G 50	34,6	2155,0	3550,0	1
13557	12 G 1,5	12,1	267,0	340,0	16						
13558	16 G 1,5	14,3	315,0	424,0	16	13594	4 G 70	41,3	3120,0	4939,0	2/0
13559	18 G 1,5	14,6	374,0	480,0	16						
13560	20 G 1,5	15,9	396,0	545,0	16	13595	4 G 95	46,2	4043,0	6690,0	3/0
13561	25 G 1,5	17,6	526,0	702,0	16						
						13596	4 G 120	51,0	5069,0	8453,0	4/0
						13597	4 G 150	59,2	5792,0	9104,0	300 kcmil

Dimensions and specifications may be changed without prior notice. (RA03)

Our Service on the Internet

Service

Through our service area, you will reach HELIS, the HELUKABEL Information System. Here you can find out the most important metal prices, receive important documents in the Download Centre, request documents and the newsletter.

www.helukabel.de