

MEGAFLEX® 600-C halogen-free, flame retardant, oil-resistant,

UV-resistant, flexible, meter marking



Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
15232	3 x 0,75	7,4	52,0	68,0	18
15233	4 G 0,75	7,9	60,0	78,0	18
15234	4 x 0,75	7,9	60,0	78,0	18
15235	5 G 0,75	9,5	71,0	95,0	18
15236	5 x 0,75	9,9	71,0	95,0	18
15237	7 G 0,75	10,0	91,0	130,0	18
15238	7 x 0,75	10,0	91,0	130,0	18
15239	12 G 0,75	13,5	142,0	203,0	18
15240	18 G 0,75	15,9	212,0	290,0	18
15241	20 G 0,75	16,9	238,0	320,0	18
15242	25 G 0,75	18,1	281,0	413,0	18
15243	2 x 1	8,0	50,0	66,0	17
15244	3 G 1	8,4	60,0	80,0	17
15245	3 x 1	8,4	60,0	80,0	17
15246	4 G 1	9,0	71,0	100,0	17
15247	4 G 1	10,0	71,0	100,0	17
15248	5 G 1	11,5	88,0	130,0	17
15249	10 G 1	14,0	150,0	232,0	17
15250	12 G 1	14,4	184,0	260,0	17
15251	18 G 1	16,9	260,0	382,0	17
15252	20 G 1	18,1	317,0	440,0	17
15253	25 G 1	20,0	349,0	540,0	17
15254	2 x 1,5	9,0	63,0	88,0	16
15255	3 G 1,5	9,2	80,0	100,0	16
15256	3 x 1,5	9,2	80,0	100,0	16
15257	4 G 1,5	10,0	97,0	125,0	16
15258	5 G 1,5	10,9	119,0	158,0	16

Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
15259	7 G 1,5	12,1	147,0	210,0	16
15260	10 G 1,5	15,1	193,0	315,0	16
15261	12 G 1,5	15,4	267,0	340,0	16
15262	18 G 1,5	18,0	374,0	480,0	16
15263	20 G 1,5	20,1	396,0	545,0	16
15264	25 G 1,5	21,4	526,0	702,0	16
15265	2 x 2,5	9,8	96,0	132,0	14
15266	3 G 2,5	10,1	144,0	168,0	14
15267	4 G 2,5	11,0	148,0	195,0	14
15268	5 x 2,5	12,0	181,0	256,0	14
15269	7 G 2,5	14,8	255,0	345,0	14
15270	10 G 2,5	17,0	340,0	482,0	14
15271	12 G 2,5	18,0	441,0	572,0	14
15272	3 G 4	11,1	174,0	251,0	12
15273	4 G 4	12,0	230,0	305,0	12
15274	5 G 4	13,9	273,0	388,0	12
15275	7 G 4	16,2	316,0	504,0	12
15276	3 G 6	13,0	240,0	351,0	10
15277	4 G 6	14,7	305,0	464,0	10
15278	5 G 6	16,0	439,0	546,0	10
15279	7 G 6	17,3	505,0	670,0	10
15280	3 G 10	17,0	350,0	574,0	8
15281	4 G 10	19,3	535,0	785,0	8
15282	5 G 10	21,7	592,0	914,0	8
15283	7 G 10	23,7	810,0	1308,0	8

Dimensions and specifications may be changed without prior notice. (RA03)

Our Service on the Internet

The screenshot shows the HELUKABEL website interface. At the top, there is a navigation menu with links for Download centre, Logistic centre, Company, Products, Quality, News, Contact, Service, Opinion, and Imprint. Below the menu, there is a search bar and a 'You are here' breadcrumb trail. A 'News' sidebar contains links for Fairs, Job posting, Special offer's, and Press Contact. The main content area features a 'Fairs' section with a dropdown menu and several images of trade fair booths. A 'HELUKABEL world-wide' section with a world map is also visible.

Trade fair appointments

In the Internet, you will find the trade fairs we are participating in, both in Germany and abroad. Please visit our Website and arrange an appointment with us. We are looking forward to your visit.

www.helukabel.de