

MULTISPEED® 500-PUR UL/CSA safety against high bending in drag chain systems, low torsion, halogen-free, meter marking



Part No.	No. cores x cross-sec. mm ²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
24387	3 G 1	18	6,0	29,0	59,0
24388	4 G 1	18	6,4	38,0	71,0
24389	5 G 1	18	7,0	48,0	84,0
24390	7 G 1	18	11,2	67,0	111,0
24391	12 G 1	18	12,3	115,0	200,0
24392	18 G 1	18	15,1	173,0	286,0
24393	25 G 1	18	17,6	240,0	370,0
24331	36 G 1	18	21,7	346,0	485,0

Part No.	No. cores x cross-sec. mm ²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
24401	4 G 2,5	14	8,9	86,0	173,0
24402	5 G 2,5	14	9,8	120,0	220,0
24403	7 G 2,5	14	16,1	168,0	290,0
24404	12 G 2,5	14	17,8	288,0	504,0
24405	18 G 2,5	14	21,8	432,0	719,0
24406	25 G 2,5	14	24,4	600,0	940,0

24394	3 G 1,5	16	6,7	43,0	81,0
24395	4 G 1,5	16	7,3	58,0	102,0
24396	5 G 1,5	16	8,0	72,0	121,0
24397	7 G 1,5	16	13,2	101,0	164,0
24398	12 G 1,5	16	14,4	173,0	293,0
24399	18 G 1,5	16	17,7	259,0	450,0
24400	25 G 1,5	16	20,5	360,0	631,0
24332	36 G 1,5	16	25,6	518,0	779,0

Dimensions and specifications may be changed without prior notice. (RN05)

Cable Glands

Cable glands for standard applications

- Plastic Glands
- Cable Glands of Brass
- Accessories

Cable glands for special application conditions

- for electromagnetic compatibility EMC
- for rugged applications and special chemical resistance
- for high temperature use
- for explosive areas
- for special mounting conditions
- for special pressure conditions



You can find cable glands in our catalogue Cable Accessories. Request it now at www.helukabel.de