

# MULTIFLEX 512®-C-PUR UL/CSA special cable for

drag chains, 80°C, 600V, two approvals control cable, EMC-preferred type, halogen-free, meter marking



Part No.	No. cores x cross-sec. mm²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
21641	2 x 0,75	18	8,8	53,0	110,0
21642	3 G 0,75	18	9,3	62,0	120,0
21643	4 G 0,75	18	9,7	77,0	148,0
21644	5 G 0,75	18	10,5	86,0	160,0
21645	7 G 0,75	18	11,9	106,0	205,0
21646	12 G 0,75	18	14,2	156,0	308,0
21647	18 G 0,75	18	16,3	233,0	420,0
21648	20 G 0,75	18	16,9	249,0	450,0
21649	25 G 0,75	18	19,2	313,0	579,0
21650	30 G 0,75	18	19,7	351,0	630,0
21651	36 G 0,75	18	21,2	400,0	745,0
21652	2 x 1	17	9,7	60,0	120,0
21653	3 G 1	17	10,0	70,0	135,0
21654	4 G 1	17	10,8	86,0	173,0
21655	5 G 1	17	11,7	99,0	187,0
21656	7 G 1	17	13,4	124,0	240,0
21657	12 G 1	17	16,0	186,0	360,0
21658	18 G 1	17	18,5	279,0	498,0
21659	20 G 1	17	19,4	322,0	568,0
21660	25 G 1	17	21,7	377,0	670,0
21661	30 G 1	17	22,5	429,0	774,0
21662	36 G 1	17	24,3	516,0	895,0
21663	41 G 1	17	26,1	610,0	1032,0
21664	50 G 1	17	28,4	690,0	1160,0
21665	65 G 1	17	32,2	852,0	1660,0
21666	2 x 1,5	16	10,2	79,0	145,0
21667	3 G 1,5	16	11,0	94,0	168,0
21668	4 G 1,5	16	11,6	113,0	217,0
21669	5 G 1,5	16	12,6	129,0	235,0
21670	7 G 1,5	16	14,5	170,0	325,0
21671	12 G 1,5	16	17,4	279,0	481,0

Part No.	No. cores x cross-sec. mm²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
21672	18 G 1,5	16	19,9	393,0	675,0
21673	25 G 1,5	16	23,7	533,0	927,0
21674	30 G 1,5	16	24,5	607,0	1025,0
21675	36 G 1,5	16	26,4	702,0	1210,0
21676	42 G 1,5	16	28,4	829,0	1441,0
21677	50 G 1,5	16	31,2	1025,0	1709,0
21678	61 G 1,5	16	34,2	1190,0	2025,0
21679	2 x 2,5	14	11,9	104,0	198,0
21680	3 G 2,5	14	12,6	129,0	284,0
21681	4 G 2,5	14	13,6	164,0	378,0
21682	5 G 2,5	14	14,7	190,0	423,0
21683	7 G 2,5	14	17,4	274,0	486,0
21684	12 G 2,5	14	20,9	426,0	756,0
21685	18 G 2,5	14	24,2	607,0	1127,0
21686	20 G 2,5	14	25,6	661,0	1210,0
21687	25 G 2,5	14	29,1	796,0	1530,0
21688	4 G 4	12	16,5	222,0	448,0
21689	5 G 4	12	18,1	328,0	533,0
21690	7 G 4	12	20,0	360,0	678,0
21691	4 G 6	10	18,1	305,0	636,0
21692	5 G 6	10	19,6	441,0	772,0
21693	7 G 6	10	23,2	505,0	1028,0
21694	4 G 10	8	22,5	485,0	1052,0
21695	5 G 10	8	24,7	610,0	1096,0
21696	7 G 10	8	29,3	820,0	1530,0
21697	4 G 16	6	25,7	840,0	1386,0
21698	5 G 16	6	28,2	1050,0	1759,0
21699	7 G 16	6	33,6	1510,0	2087,0

Dimensions and specifications may be changed without prior notice. (RN05)



Photo: KASTO Maschinenbau GmbH & Co.KG

N