

MULTISPEED® 500-TPE UL/CSA high flexible,

safety against high bending in drag chain systems, low torsion,

halogen-free, meter marking



Part No.	No. cores x cross-sec. mm ²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
24468	2 x 1	18	5,2	19,2	50,0
24469	3 G 1	18	5,9	29,0	60,0
24470	4 G 1	18	6,4	38,0	74,0
24471	5 G 1	18	7,0	48,0	86,0
24472	7 G 1	18	11,2	67,0	114,0
24473	12 G 1	18	12,3	115,0	210,0
24474	18 G 1	18	15,1	173,0	291,0
24475	25 G 1	18	17,6	240,0	380,0
24476	3 G 1,5	16	6,7	43,0	84,0
24477	4 G 1,5	16	7,3	58,0	108,0
24478	5 G 1,5	16	8,0	72,0	126,0

Part No.	No. cores x cross-sec. mm ²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
24479	7 G 1,5	16	13,2	101,0	169,0
24480	12 G 1,5	16	14,4	173,0	299,0
24481	18 G 1,5	16	17,7	259,0	460,0
24482	25 G 1,5	16	19,8	360,0	640,0
24483	4 G 2,5	14	8,9	96,0	179,0
24484	5 G 2,5	14	9,8	120,0	230,0
24485	7 G 2,5	14	16,1	168,0	294,0
24486	12 G 2,5	14	17,8	288,0	510,0
24487	18 G 2,5	14	21,8	432,0	722,0
24488	25 G 2,5	14	24,4	600,0	950,0

Dimensions and specifications may be changed without prior notice. (RN05)

Tools

- Cable shears
- Box spanners
- Strippers
- Crimping tools
- Pliers
- Skinning knife



You can find tools in our catalogue Cable Accessories.
Request it now at www.helukabel.de



N