

MULTISPEED® 500-C-TPE UL/CSA safety

against high bending in drag chain systems, low torsion, halogen-free,

EMC-preferred type, meter marking



Part No.	No. cores x cross-sec. mm ²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
23931	2 x 1	18	7,4	50,0	115,0
23932	3 G 1	18	7,7	59,0	131,0
23933	4 G 1	18	8,3	70,0	160,0
23934	5 G 1	18	9,1	84,0	195,0
23935	7 G 1	18	14,0	106,0	247,0
23936	12 G 1	18	15,0	174,0	411,0
23937	18 G 1	18	18,5	240,0	547,0
23938	25 G 1	18	21,4	352,0	754,0

Part No.	No. cores x cross-sec. mm ²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
23939	3 G 1,5	16	8,6	75,0	160,0
23940	4 G 1,5	16	9,4	90,0	194,0
23941	5 G 1,5	16	10,4	108,0	220,0
23942	7 G 1,5	16	16,0	157,0	294,0
23943	12 G 1,5	16	17,6	240,0	490,0
23944	18 G 1,5	16	21,3	355,0	704,0
23945	25 G 1,5	16	24,8	448,0	930,0
23946	4 G 2,5	14	11,3	134,0	260,0
23947	5 G 2,5	14	12,3	175,0	330,0
23948	7 G 2,5	14	14,8	229,0	406,0
23949	12 G 2,5	14	21,5	390,0	990,0

Dimensions and specifications may be changed without prior notice. (RN05)

Core end sleeves and cable lugs

- Core end sleeves
- Solderless terminals
- Tubular cable lugs
- Compression joints



N



You can find core end sleeves and cable lugs in our catalogue Cable Accessories. Request it now at www.helukabel.de