

TOPSERV® 113 / 127 according to

Siemens-Standard 6FX 8008- bzw. 6FX 7008-, high flexible drag chain
servo cable, 0,6/1kV, meter marking



TOPSERV® 113 according to SIEMENS Standard 6FX 8008-

Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
74508	(4 x 4 + (2 x 1,0))	15,0	258,0	462,0	12
78950	(4 x 4 + (2 x 1,5))	15,0	268,0	475,0	12
74514	(4 x 6 + (2 x 1,0))	16,1	348,0	596,0	10
78951	(4 x 6 + (2 x 1,5))	16,3	358,0	607,0	10
74509	(4 x 10 + (2 x 1,0))	20,2	574,0	912,0	8
78952	(4 x 10 + (2 x 1,5))	21,5	584,0	922,0	8
74510	(4 x 16 + (2 x 1,0))	23,8	815,0	1194,0	6
75956	(4 x 16 + (2 x 1,5))	24,8	825,0	1205,0	6
74511	(4 x 25 + (2 x 1,0))	27,0	1273,0	1499,0	4
75957	(4 x 25 + (2 x 1,5))	27,5	1283,0	1510,0	4
74512	(4 x 35 + (2 x 1,0))	31,9	1840,0	1992,0	2
75958	(4 x 35 + (2 x 1,5))	31,6	1850,0	2005,0	2
74513	(4 x 50 + (2 x 1,0))	36,7	2530,0	2880,0	1
75959	(4 x 50 + (2 x 1,5))	36,7	2540,0	2890,0	1

Dimensions and specifications may be changed without prior notice. (RN07)

Marking

Marking rings
Cable marker
Indian pen



You can find marking in our catalogue Cable Accessories.
Request it now at www.helukabel.de