

TOPFLEX®-EMV-UV-2YSLCYK-J UL/CSA Motor

supply cable 0,6/1kV, for power supply connections to frequency converters, double screened, meter marking.



Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Mutual capacitance		Coupling resistance		Power ratings **) with 3 loaded cores in Ampère	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
			core/core ca. nF/km	core/shield ca. nF/km	with 1 MHz Ohm/km	with 30 MHz Ohm/km				
22328	(4 x 50)	35,2	190,0	320,0	2,0	40,0	168,0	2345,0	2950,0	1
22329	(4 x 70)	41,4	190,0	320,0	2,0	45,0	207,0	3196,0	3950,0	2/0
22330	(4 x 95)	46,0	250,0	410,0	1,0	50,0	250,0	4316,0	5300,0	3/0
22331	(4 x 120)	50,8					292,0	5435,0	6600,0	4/0
22332	(4 x 150)	58,3					335,0	6394,0	7040,0	300 kcmil
22333	(4 x 185)	65,5					382,0	7639,0	8380,0	350 kcmil

Dimensions and specifications may be changed without prior notice. (RD01)

Bundling, binding, fastening

- Plastic helix
- Cable tie
- Hook and loop cable tie
- Mounting block



You can find bundling, binding, fastening in our catalogue Cable Accessories. Request it now at www.helukabel.de