

TOPFLEX®-EMV-UV-3 PLUS 2YSLCYK-J

UL/CSA Motor supply cable 0,6/1kV, for power supply connections to frequency converters, double screened, meter marking.



Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Coupling resistance		Power ratings **) with 3 loaded cores in Ampère	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
			with 1 MHz Ohm/km	with 30 MHz Ohm/km				
22193	(3 x 1,5 + 3 x 0,25)	10,0			18,0	86,0	140,0	16
22194	(3 x 2,5 + 3 x 0,5)	11,4	18,0	210,0	26,0	144,0	220,0	14
22195	(3 x 4 + 3 x 0,75)	13,0	11,0	210,0	34,0	224,0	323,0	12
22196	(3 x 6 + 3 x 1,0)	15,0	6,0	150,0	44,0	298,0	420,0	10
22197	(3 x 10 + 3 x 1,5)	18,4	7,0	180,0	61,0	491,0	615,0	8
22198	(3 x 16 + 3 x 2,5)	21,0	9,0	190,0	82,0	723,0	819,0	6
22199	(3 x 25 + 3 x 4,0)	25,3	4,0	95,0	108,0	1138,0	1325,0	4
22223	(3 x 35 + 3 x 6,0)	27,8	3,0	85,0	135,0	1535,0	1718,0	2
22224	(3 x 50 + 3 x 10,0)	32,6	2,0	40,0	168,0	2208,0	2399,0	1
22225	(3 x 70 + 3 x 10,0)	38,1	2,0	45,0	207,0	2871,0	3056,0	2/0
22226	(3 x 95 + 3 x 16,0)	41,0	1,0	50,0	250,0	3953,0	4162,0	3/0
22227	(3 x 120 + 3 x 16,0)	46,4			292,0	4836,0	5075,0	4/0
22228	(3 x 150 + 3 x 25,0)	53,5			335,0	5412,0	6128,0	300 kcmil
22229	(3 x 185 + 3 x 35,0)	59,5			382,0	6969,0	7189,0	350 kcmil
22230	(3 x 240 + 3 x 42,5)	65,1				8540,0	9540,0	500 kcmil

Dimensions and specifications may be changed without prior notice. (RD01)

Terminations and straight-through joints

Telephone cables
Low voltage
Medium voltage
Accessories



You can find terminations and straight-through joints in our catalogue Cable Accessories. Request it now at www.helukabel.de