

TOPFLEX®-MOTOR-EMV 103 low capacitance power

supply cable 0,6/1kV, increased ampacity, meter marking



Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.	Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
22689	(3 x 1,5)	9,4	72,0	200,0	16	22698	(5 x 4)	15,4	321,0	567,0	16
22690	(4 x 1,5)	10,4	95,0	230,0	16	22699	(7 x 4)	18,2	352,0	603,0	16
22691	(5 x 1,5)	11,2	117,0	258,0	16	22700	(4 x 6)	15,2	320,0	633,0	16
22692	(7 x 1,5)	13,2	148,0	281,0	16	22701	(5 x 6)	16,8	439,0	679,0	16
22693	(3 x 2,5)	11,2	137,0	270,0	16	22702	(7 x 6)	20,0	501,0	771,0	16
22694	(4 x 2,5)	12,5	150,0	300,0	16	22703	(4 x 10)	19,5	533,0	860,0	16
22695	(5 x 2,5)	13,5	200,0	352,0	16	22704	(5 x 10)	21,6	711,0	1029,0	16
22696	(7 x 2,5)	16,0	230,0	473,0	16	22705	(4 x 16)	23,1	789,0	1290,0	16
22697	(4 x 4)	14,2	235,0	485,0	16	22706	(4 x 25)	27,1	1236,0	1862,0	16

Dimensions and specifications may be changed without prior notice. (RN07)

Drag Chain Systems

- Open chains
- Closed chains
- Accessories
- Installation instructions
- Selection tables



You can find drag chain systems in our catalogue Cable Accessories.
Request it now at www.helukabel.de