

Contents

Description	Page
Power Cables	
NY Y-J / NY Y-O, power cable, 0,6/1kV, VDE approved	Q 6
NAYY, power cable, 0,6/1 kV, VDE approved	Q 8
NYCY, power cable, 0,6/1kV, VDE approved, with concentric copper conductor	Q 9
NYCWY, power cable, 0,6/1kV, with concentric copper conductor, VDE approved	Q 11
A-LiY(StE)YÖ, Data transmission cables for petrol stations and refineries with BAM*-test report	Q 13
Petrol Station Cables, (N)YYÖ-J 0,6/1 kV, with BAM-test report	Q 14
NYKY-J 0,6/1kV, with lead sheath, VDE approved	Q 15
Security Cables	
N2XH, power cable, 0,6/1 kV, halogen-free, without functionality	Q 18
N2XCH, power cable, 0,6/1kV, halogen-free, with concentric conductor, without functionality	Q 20
JE-H(St)H, Bd FE 180/E 30 bis E 90 (orange), halogen-free	Q 22
JE-H(St)H, Bd fire warning cable, FE 180/E 30 to E 90 (red), halogen-free	Q 23
JE-H(St)HRH, Bd fire warning cable, FE 180/E 30 to E 90, halogen-free	Q 24
N2XH-FE 180/E 30, security cable, halogen-free, 0,6/1 kV, with improved fire characteristics	Q 25
N2XCH-FE 180/E 30, security cable, halogen-free, 0,6/1 kV, with improved fire characteristics	Q 27
NHXH-FE 180/E 30, security cable, halogen-free, 0,6/1 kV, with improved fire characteristics	Q 29
NHXCH-FE 180/E 30, security cable, halogen-free, 0,6/1 kV, with improved fire characteristics	Q 31
N2XH-FE 180/E 90, security cable, halogen-free, 0,6/1 kV, with improved fire characteristics	Q 33
N2XCH-FE 180/E 90, security cable, halogen-free, 0,6/1 kV, with improved fire characteristics	Q 35
NHXH-FE 180/E 90, security cable, halogen-free, 0,6/1 kV, with improved fire characteristics	Q 37
NHXCH-FE 180/E 90, security cable, halogen-free, 0,6/1 kV, with improved fire characteristics	Q 39
Medium Voltage Power Cables	
N2XSY 6/10kV, 12/20kV, 18/30kV, XLPE-insulated, Cu-conductor, single core, screened, PVC-jacket	Q 44
NA2XSY 6/10kV, 12/20kV, 18/30kV, XLPE-insulated, alu-conductor, single core, screened, PVC-jacket	Q 46
N2XS2Y 6/10kV, 12/20kV, 18/30kV, XLPE-insulated, Cu-conductor, single core, screened, PE-jacket	Q 48
NA2XS2Y 6/10kV, 12/20kV, 18/30kV, XLPE-insulated, Cu-conductor, single core, screened, PE-jacket	Q 50
N2XS(F)2Y 6/10kV, 12/20kV, 18/30kV, XLPE-insulated, Cu-conductor, single core, longitudinally water-tight, screened, PE-jacket	Q 52
NA2XS(F)2Y 6/10kV, 12/20kV, 18/30kV, XLPE-insulated, alu-conductor, single core, longitudinally water-tight, screened, PE-jacket	Q 54
N2XSEY 3 x ... 6/10kV, XLPE-insulated, Cu-conductor, PVC-jacket	Q 56