

N2XH power cable, 0,6/1 kV, halogen-free, without functionality



Part No. J type	O type	No. cores x cross-sec. mm²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.	Part No. J type	O type	No. cores x cross-sec. mm²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
53149	53290	4 x 25 rm	25,0	960,0	1440,0	4	53136	53330	3 x 50 / 25 rm	28,5	1680,0	2100,0	1
53150	53291	4 x 35 rm	27,0	1344,0	1890,0	2	53137	53331	3 x 70 / 35 rm	31,4	2352,0	2800,0	2/0
53151	53292	4 x 50 rm	28,0	1920,0	2300,0	1	53138	53332	3 x 95 / 50 rm	34,9	3216,0	3750,0	3/0
53152	53293	4 x 70 rm	32,0	2668,0	3200,0	2/0	53139	53333	3 x 120 / 70 rm	38,0	4128,0	4750,0	4/0
53153	53294	4 x 95 rm	36,0	3648,0	4250,0	3/0	53140	53334	3 x 150 / 70 rm	43,3	4992,0	5750,0	300 kcmil
53154	53295	4 x 120 rm	40,2	4608,0	5350,0	4/0	53141	53335	3 x 185 / 95 rm	47,2	6240,0	7200,0	350 kcmil
53155	53296	4 x 150 rm	45,8	5760,0	6550,0	300 kcmil	53142	53336	3 x 240 / 120 rm	53,4	8064,0	9300,0	500 kcmil
53156	53297	4 x 185 rm	49,5	7104,0	8100,0	350 kcmil							
53157	53298	4 x 240 rm	56,0	9216,0	10550,0	500 kcmil							
53158	53299	5 x 1,5 re	14,5	72,0	280,0	16							
53159	53309	5 x 2,5 re	16,0	120,0	350,0	14							
53160	53310	5 x 4 re	17,0	192,0	450,0	12							
53161	53311	5 x 6 re	18,5	288,0	600,0	10							
53162	53312	5 x 10 re	21,0	480,0	850,0	8							
53163	53313	5 x 16 re	24,0	768,0	1200,0	6							
53164	53314	7 x 1,5 re	15,5	101,0	350,0	16							
53171	53315	7 x 2,5 re	17,0	168,0	370,0	14							
53178	53316	7 x 4 re	17,2	269,0	530,0	12							
53165	53317	10 x 1,5 re	18,5	144,0	480,0	16							
53172	53318	10 x 2,5 re	20,0	240,0	500,0	14							
53166	53319	12 x 1,5 re	19,0	173,0	520,0	16							
53173	53320	12 x 2,5 re	21,0	288,0	560,0	14							
53179	53321	12 x 4 re	21,2	461,0	800,0	12							
53167	53322	14 x 1,5 re	20,0	202,0	550,0	16							
53174	53323	14 x 2,5 re	22,0	336,0	630,0	14							
53168	53324	19 x 1,5 re	22,0	274,0	700,0	16							
53175	53325	19 x 2,5 re	24,0	456,0	800,0	14							
53169	53326	24 x 1,5 re	25,0	346,0	850,0	16							
53176	53327	24 x 2,5 re	27,0	576,0	990,0	14							
53170	53328	30 x 1,5 re	26,0	432,0	950,0	16							
53177	53329	30 x 2,5 re	28,0	720,0	1180,0	14							

Dimensions and specifications may be changed without prior notice. (RQ02)

Our Service on the Internet

The screenshot shows the HELUKABEL website interface. At the top, there are navigation links: Download centre, Logistic centre, Company, Products, Quality, News, Contact, Service, Opinion, and Imprint. The main content area features a 'Contact' sidebar with options for Headquarters Hemmingen, Approach, and Contact person. The 'Contact person' section includes a text prompt: 'In order to respond to your request for: HELUKABEL@ contact person in'. Below this is a 'Post code search for Germany' section with a text input field and a button labeled 'Finden Sie Ihren Ansprechpartner'. On the right, there is a 'HELUKABEL world-wide' section with a world map and a 'please select...' dropdown menu.

Contact person

Enter your postal code to find out your personal customer sales consultant, who serves as your contact for questions and offers. Simply click and check it out. We are looking forward to hearing from you.

www.helukabel.de