

N2XCH power cable, 0,6/1kV, halogen-free, with concentric conductor, without functionality



Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
53234	12 x 1,5 / 2,5 re	18,4	204,0	460,0	16
53241	12 x 2,5 / 4 re	19,2	335,0	610,0	14
53247	12 x 4 / 6 re	22,6	528,0	910,0	12
53235	16 x 1,5 / 4 re	20,0	275,0	686,0	16
53242	16 x 2,5 / 6 re	20,9	450,0	805,0	14

Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
53236	21 x 1,5 / 6 re	22,6	370,0	766,0	16
53243	21 x 2,5 / 6 re	25,2	572,0	1015,0	14
53237	24 x 1,5 / 6 re	23,2	412,0	800,0	16
53244	24 x 2,5 / 10 re	26,1	695,0	1100,0	14
53238	30 x 1,5 / 6 re	24,3	500,0	930,0	16
53245	30 x 2,5 / 10 re	28,0	842,0	1290,0	14

Dimensions and specifications may be changed without prior notice. (RQ02)

Cable Glands

Cable glands for standard applications

- Plastic Glands
- Cable Glands of Brass
- Accessories

Cable glands for special application conditions

- for electromagnetic compatibility EMC
- for rugged applications and special chemical resistance
- for high temperature use
- for explosive areas
- for special mounting conditions
- for special pressure conditions



You can find cable glands in our catalogue Cable Accessories.
Request it now at www.helukabel.de