

N2XH-FE 180/E 30 security cable, halogen-free, 0,6/1 kV, with improved fire characteristics



Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.	Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
52068	1 x 150 rm	23,0	1440,0	1650,0	300 kcmil	52094	3 G 150 / 70 rm	48,5	4992,0	6560,0	300 kcmil
52069	1 x 185 rm	25,0	1776,0	2030,0	350 kcmil	52095	3 G 185 / 95 rm	54,0	6240,0	8240,0	350 kcmil
52070	1 x 240 rm	29,0	2304,0	2590,0	500 kcmil						
52071	2 x 1,5 re	11,5	29,0	170,0	16	52096	4 G 1,5 re	12,5	58,0	210,0	16
52072	2 x 2,5 re	12,0	48,0	190,0	14	52097	4 G 2,5 re	13,0	96,0	260,0	14
52073	2 x 4 re	13,0	77,0	260,0	12	52614	4 G 4 re	13,0	154,0	310,0	12
52074	2 x 6 re	14,0	115,0	310,0	10	52615	4 G 6 re	14,5	230,0	410,0	10
52075	2 x 10 re	15,5	192,0	430,0	8	52616	4 G 10 re	16,0	384,0	620,0	8
52076	2 x 16 re	17,5	307,0	600,0	6	52617	4 G 16 re	18,0	614,0	900,0	6
52077	2 x 25 rm	22,0	480,0	930,0	4	52628	4 x 25 rm	23,6	960,0	1600,0	4
52078	3 G 1,5 re	12,0	43,0	170,0	16	52629	4 x 35 rm	26,4	1344,0	2050,0	2
52079	3 G 2,5 re	12,5	72,0	220,0	14	52383	4 x 50 rm	29,5	1920,0	2761,0	1
52080	3 G 4 re	13,5	115,0	290,0	12	52432	4 x 70 rm	34,6	2688,0	3785,0	2/0
52081	3 G 6 re	14,5	173,0	370,0	10	52433	4 x 95 rm	39,0	3648,0	5010,0	3/0
52082	3 G 10 re	16,5	288,0	530,0	8	52434	4 x 120 re	43,5	4608,0	6135,0	4/0
52083	3 G 16 re	18,5	461,0	760,0	6						
52084	3 G 25 rm	23,5	720,0	1160,0	4	52618	5 G 1,5 re	12,0	72,0	210,0	16
52088	3 G 25 / 16 rm	22,5	874,0	1430,0	4	52619	5 G 2,5 re	13,0	120,0	280,0	14
52085	3 G 35 rm	26,0	1080,0	1560,0	2	52620	5 G 4 re	14,5	192,0	380,0	12
52089	3 G 35 / 16 rm	28,0	1162,0	1810,0	2	52621	5 G 6 re	15,5	288,0	510,0	10
52086	3 G 50 rm	29,0	1440,0	2030,0	1	52622	5 G 10 re	18,0	480,0	760,0	8
52090	3 G 50 / 25 rm	32,0	1680,0	2340,0	1	52623	5 G 16 re	20,0	768,0	1120,0	6
52087	3 G 70 rm	34,0	2016,0	2890,0	2/0	52626	5 x 25 rm	24,5	1200,0	1840,0	4
52091	3 G 70 / 35 rm	35,0	2352,0	3190,0	2/0	52627	5 x 35 rm	33,5	1680,0	2510,0	2
52092	3 G 95 / 50 rm	40,0	3216,0	4350,0	3/0	52624	7 G 1,5 re	13,0	101,0	250,0	16
52093	3 G 120 / 70 rm	45,0	4128,0	5550,0	4/0	52625	12 G 1,5 re	16,5	173,0	390,0	16

Dimensions and specifications may be changed without prior notice. (RQ02)

Our Service on the Internet

Download centre Logistic centre

Company Products Quality News Contact Service Opinion Imprint



You are here: Home Contact Approach

- Contact
- Headquarters Hemmingen
- Approach
- Contact person

Approach

To get in touch with us, we kindly ask you to fill out the following form.
Your data will be handled confidentially and will not be passed to any third party.

We will get in touch with you as soon as possible!

- Subsidiaries and Agencies
- Headquarters Hemmingen
- Approach
- Contact person

Search



Making contact

Your direct line to us. Here you can enter your most important contact data as well as the product area, also any information you would like. We will call you back as soon as possible.

www.helukabel.de