

N2XCH-FE 180/E 90 security cable, halogen-free, 0,6/1 kV, with improved fire characteristics

Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.	Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
52781	3 x 95 / 50 rm	43,0	3296,0	4700,0	3/0	52797	4 x 120 / 70 rm	52,5	5388,0	7340,0	4/0
52782	3 x 120 / 70 rm	48,0	4236,0	5880,0	4/0	52798	4 x 150 / 70 rm	57,5	6540,0	8840,0	300 kcmil
52783	3 x 150 / 70 rm	52,0	4992,0	7300,0	300 kcmil	52799	4 x 185 / 95 rm	63,5	8159,0	11020,0	350 kcmil
52784	3 x 185 / 95 rm	57,5	6383,0	8760,0	350 kcmil	52800	4 x 240 / 120 rm	70,0	10546,0	14140,0	500 kcmil
52785	3 x 240 / 120 rm	63,5	8242,0	11280,0	500 kcmil						
52786	4 x 1,5 / 1,5 re	17,5	81,0	390,0	16	52801	7 x 1,5 / 2,5 re	20,5	133,0	520,0	16
52787	4 x 2,5 / 2,5 re	19,0	128,0	470,0	14	52805	7 x 2,5 / 2,5 re	22,0	200,0	630,0	14
52788	4 x 4 / 4 re	20,0	200,0	570,0	12	52802	12 x 1,5 / 2,5 re	26,0	205,0	770,0	16
52789	4 x 6 / 6 re	21,5	297,0	720,0	10	52806	12 x 2,5 / 4 re	28,0	334,0	950,0	14
52790	4 x 10 / 10 rm	24,0	504,0	1010,0	8						
52791	4 x 16 / 16 rm	26,5	796,0	1370,0	6	52803	24 x 1,5 / 6 re	35,0	413,0	1380,0	16
52792	4 x 25 / 16 rm	30,5	1142,0	1940,0	4	52807	24 x 2,5 / 10 re	37,5	696,0	1750,0	14
52793	4 x 35 / 16 rm	33,0	1526,0	2420,0	2						
52794	4 x 50 / 25 rm	37,5	2203,0	3240,0	1	52804	30 x 1,5 / 6 re	37,0	499,0	1630,0	16
52795	4 x 70 / 35 rm	41,5	3082,0	4360,0	2/0	52808	30 x 2,5 / 10 re	39,5	840,0	2080,0	14
52796	4 x 95 / 50 rm	47,5	4208,0	5900,0	3/0						

Dimensions and specifications may be changed without prior notice. (RQ02)

Tools

- Cable shears
- Box spanners
- Strippers
- Crimping tools
- Pliers
- Skinning knife



You can find tools in our catalogue **Cable Accessories**.
Request it now at www.helukabel.de