

N2XSY 6/10kV, 12/20kV, 18/30kV XLPE-insulated,

Cu-conductor, single core, screened, PVC-jacket



Part No.	No. cores x cross-sec. mm ²	Operation voltage max.	Nominal voltage kV	Insulation thickness mm	Jacket thickness mm	Outer ø min - max mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
32428	1 x 50 rm / 16	36	18 / 30	8,0	2,5	33,0 - 38,0	662,0	1480,0	1
32429	1 x 70 rm / 16	36	18 / 30	8,0	2,5	35,0 - 40,0	854,0	1730,0	2/0
32430	1 x 95 rm / 16	36	18 / 30	8,0	2,5	36,0 - 41,0	1094,0	2060,0	3/0
32431	1 x 120 rm / 16	36	18 / 30	8,0	2,5	38,0 - 43,0	1334,0	2330,0	4/0
32432	1 x 150 rm / 25	36	18 / 30	8,0	2,5	39,0 - 44,0	1725,0	2720,0	300 kcmil
32433	1 x 185 rm / 25	36	18 / 30	8,0	2,5	41,0 - 46,0	2059,0	3100,0	350 kcmil
32434	1 x 240 rm / 25	36	18 / 30	8,0	2,5	43,0 - 48,0	2587,0	3730,0	500 kcmil
32435	1 x 300 rm / 25	36	18 / 30	8,0	2,5	46,0 - 51,0	3163,0	4000,0	600 kcmil
32436	1 x 400 rm / 35	36	18 / 30	8,0	2,5	49,0 - 54,0	4234,0	5330,0	750 kcmil
32437	1 x 500 rm / 35	36	18 / 30	8,0	2,5	52,0 - 57,0	5194,0	6480,0	1000 kcmil

Dimensions and specifications may be changed without prior notice. (RQ03)

Marking

Marking rings
Cable marker
Indian pen



You can find marking in our catalogue Cable Accessories.
Request it now at www.helukabel.de

