

# NA2XS2Y 6/10kV, 12/20kV, 18/30kV XLPE-insulated,

Cu-conductor, single core, screened, PE-jacket



Part No.	No. cores x cross-sec. mm <sup>2</sup>	Operation voltage max.	Nominal voltage kV	Insulation thickness mm	Jacket thickness mm	Outer ø min - max mm	Cop. weight kg / km	Alu weight kg / km	Weight ca. kg / km	AWG-No.
32546	1 x 50 rm / 16	36	18 / 30	8,0	2,5	33,0 - 38,0	182,0	145,0	1120,0	1
32547	1 x 70 rm / 16	36	18 / 30	8,0	2,5	35,0 - 40,0	182,0	203,0	1270,0	2/0
32548	1 x 95 rm / 16	36	18 / 30	8,0	2,5	36,0 - 41,0	182,0	276,0	1380,0	3/0
32549	1 x 120 rm / 16	36	18 / 30	8,0	2,5	38,0 - 43,0	182,0	348,0	1530,0	4/0
32550	1 x 150 rm / 25	36	18 / 30	8,0	2,5	39,0 - 44,0	283,0	435,0	1720,0	300 kcmil
32551	1 x 185 rm / 25	36	18 / 30	8,0	2,5	41,0 - 46,0	283,0	537,0	1860,0	350 kcmil
32552	1 x 240 rm / 25	36	18 / 30	8,0	2,5	43,0 - 48,0	283,0	696,0	2110,0	500 kcmil
32553	1 x 300 rm / 25	36	18 / 30	8,0	2,5	46,0 - 51,0	283,0	870,0	2370,0	600 kcmil
32554	1 x 400 rm / 35	36	18 / 30	8,0	2,5	49,0 - 54,0	394,0	1160,0	2820,0	750 kcmil
32555	1 x 500 rm / 35	36	18 / 30	8,0	2,5	52,0 - 57,0	394,0	1450,0	3280,0	1000 kcmil

Dimensions and specifications may be changed without prior notice. (RQ03)

## Insulating, shrinking, braided and temperature protection tubes

**Braided hoses**  
**High temperature protection**  
**Insulation tubes**  
**Heat-shrink tubes**  
**End caps**



You can find insulating, shrinking, braided and temperature protection tubes in our catalogue **Cable Accessories**. Request it now at [www.helukabel.de](http://www.helukabel.de)