

N2XS(F)2Y 6/10kV, 12/20kV, 18/30kV XLPE-insulated, Cu-conductor, single core, longitudinally water-tight, screened, PE-jacket



Part No.	No. cores x cross-sec. mm ²	Operation voltage max.	Nominal voltage kV	Insulation thickness mm	Screen cross-sec. mm ²	Jacket thickness mm	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
32582	1 x 50 rm / 16	36	18 / 30	8,0	16,0	2,5	37,0	662,0	1700,0	1
32583	1 x 70 rm / 16	36	18 / 30	8,0	16,0	2,5	38,0	854,0	1950,0	2/0
32584	1 x 95 rm / 16	36	18 / 30	8,0	16,0	2,5	40,0	1094,0	2300,0	3/0
32585	1 x 120 rm / 16	36	18 / 30	8,0	16,0	2,5	42,0	1334,0	2600,0	4/0
32586	1 x 150 rm / 25	36	18 / 30	8,0	25,0	2,5	43,0	1723,0	3000,0	300 kcmil
32587	1 x 185 rm / 25	36	18 / 30	8,0	25,0	2,5	45,0	2059,0	3350,0	350 kcmil
32588	1 x 240 rm / 25	36	18 / 30	8,0	25,0	2,5	47,0	2587,0	4100,0	500 kcmil
32589	1 x 300 rm / 25	36	18 / 30	8,0	25,0	2,5	50,0	3163,0	4800,0	600 kcmil
32590	1 x 400 rm / 35	36	18 / 30	8,0	35,0	2,5	53,0	4234,0	5750,0	750 kcmil
32591	1 x 500 rm / 35	36	18 / 30	8,0	35,0	2,5	56,0	5194,0	6700,0	1000 kcmil

Dimensions and specifications may be changed without prior notice. (RQ03)

Drag Chain Systems

Open chains
Closed chains
Accessories
Installation instructions
Selection tables



You can find drag chain systems in our catalogue Cable Accessories.
Request it now at www.helukabel.de